

# FLOS

 F1130039 Glossy Green

## Bellhop Unplugged


Designed by Edward Barber and Jay Osgerby, 2018



2W - 87lm - 2200-2700-3000K - CRI> 90

Portable table lamp emitting direct light. Features a polycarbonate (PC) base and dome with an opaline, injection-moulded, photo-engraved PC diffuser. The base houses a push-button switch with 4-step dimming, 3-step colour temperature selection and a battery status indicator. Provides up to 24 hours of use. IP54 protection rating for outdoor use. Rechargeable via USB-C. Charging cable included.

Originally designed in 2016 as a bespoke table light for the Parabola restaurant and members' room at the Design Museum in London, Bellhop has since become a contemporary essential. Created for everyday use in any setting, its iconic bell-shaped diffuser evokes the warm glow of a modern-day candle, bringing soft, atmospheric light wherever needed.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)


### Main specifications

EAN	8059607080801
Mounting	Portable
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED Module
Number of lamps	1
Power (W)	2
Source flux (lm)	87
Lumen Output (lm)	87

### Physical

Colour	Glossy Green
Length (mm)	125
Net weight (kg)	0.75
Package height (mm)	200
Package width (mm)	200
Package length (mm)	330
Package volume (m3)	0.01
IP internal	54

### Download

[Mounting instructions](#)  PDF

### Photometric Files

[LDT / IES](#)  LDT


### Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



## Schematic light drawing



## Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	2200-2700-3000
CRI>	90
LED Life / Failure Ratio	30000
Extreme cut off	No

## Electrical


Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	5
Power supply	Remote excluded
Dimmable	Yes
Dimming interface	Dimmer Integrated
Induction recharge Qi	No
Batteries inside	Yes
Battery type	LI-IO
Charging cycles guaranteed	1000
Charging min time	4
Charging socket/connector	USB-C

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class C



Non-replaceable light source





Replaceable control gear by an end-user

## Spare Parts

01. Bellhop TW Battery pack

RF38035



(\*) The battery kit is only compatible with the new "TW" models. It is not backward compatible with older product versions.



RF38035

Bellhop TW Battery pack