

# Flock Chandelier Giant installation instructions

THREE PERSONS REQUIRED, TAKING APPROXIMATELY 50 MINUTES

\* Installation should be carried out in accordance and compliance to current building regulations. Please ensure to isolate the mains power upon fitment \*

1. Extremely Fragile. Please treat this like thin fragile glass when unpacking and installing.
2. Carefully remove the top pieces of cardboard from the chandelier box so the top of the chandelier plate is exposed.
3. Using the cup hooks provided, screw these into the ceiling next to where the chandelier will hang, screwing them equally distanced apart around the central point of where the chandelier will be secured.
4. Using the elasticated bungees provided, hook these over the cup hooks which are attached to the top of the chandelier plate.
5. With two people, carefully lift up the chandelier and attach the other end of the bungees to the cup hooks on the ceiling, placing each of the bungee hooks over top of each cup hook secured into the ceiling.
6. Wire in the three protruding braided flex wires from the centre of the chandelier to the mains electricity.
7. Uncoil as many of the threads which attach to the steam bent wooden components as you need to allow you access to the centre of the underside of the chandelier plate.
8. With two people holding the chandelier plate, remove all of the bungees and cup hooks from both the ceiling and the chandelier plate; the chandelier can now be pushed against the ceiling, exactly in the desired position.
9. Screw in the 80mm screws (or your own depending on the ceiling structure) into the ceiling through the four 12mm holes near the centre of the chandelier plate; the chandelier weighs around 5kg; it is vital it is secured to a structural section/ beam in the ceiling. Be very careful here not to tangle or get the threads caught in the drill driver.
10. Use the wooden plugs/end caps to push into the screw holes to conceal the screws. Some super glue/ wood glue (not supplied) carefully applied to the plugs will ensure it does not fall out with time.
11. Carefully uncoil and un-wrap all of the other hanging parts, untangling any which may have become tangled during installation.
12. Attach the light bulbs provided.