
IN/ADER

The ultimate mobility scooter





IN/ADER The ultimate mobility scooter



Learn more about your Invader today...

Contents

1	Welcome6				
2	Legal7				
3	Safe	ty8			
	3.1	Safe Inclines9			
4	Intro	pduction			
5	You	r Invader11			
	5.1	Intended Use11			
	5.2	Unintentional Movement12			
6	Exte	rior Guide13			
		Handlebar Controls Guide14			
7	Han	dlebar Controls Guide14			
7 8		dlebar Controls Guide14 rating Your Invader			
,					
,	Ope	rating Your Invader15			
,	Ope 8.1	rating Your Invader			
,	Ope 8.1 8.2	rating Your Invader			

	8.5.1	Turning On	18
	8.5.2	Steering Lock	18
	8.6	Acceleration & Braking	19
	8.6.1	Accelerating	19
	8.6.2	Engaging the Brake Lock	20
	8.6.3	Reversing	20
	8.7	Digital LCD Display	22
	8.8	Lights	23
	8.9	Indicators	23
	8.10	Follow-Me-Home Lights	23
	8.11	Horn	24
	8.12	Charging the Invader	25
9	Mair	ntenance	26
	9.1	Replacing Bulbs	26
	9.2	Battery Care	26
	9.3	Isolation Switches	27
	9.4	Tyre Pressures	28
	9.5	Troubleshooting	29

9.6		Maintenance	.30
	9.6.1	Cleaning	.30
10 Warranty		anty	.31
1	0.1	One-Year Warranty	.31
1	0.2	Warranty Exclusions	.31
1	0.3	Warranty Policy	.32
11 Specifications		.33	

1	11.1 Technical Specification		33
1	1.2	Sizes & Weights	34
12	2 Servicing		35
13	13 Notes		39

1 Welcome

Congratulations on purchasing your Scooterpac Invader. With regular maintenance and proper operation your Invader will give you many years and countless miles of rewarding experiences. This manual contains the information that you and your authorised Scooterpac service centre will need to keep your Invader in good working order.

If you have any questions, please contact the Scooterpac dealer that supplied your Invader and they will be happy to help you.

Please fully charge your scooter, at least once a week to maintain battery life & maximise performance. Even when the scooter isn't in use.

This Invader was originally supplied by:

Dealer Name	
Address 1	
Address 2	
Town/City	
Postcode	
Phone Number	
E-mail Address	
Website	

2 Legal

The **Invader** is designed to be operated by a single person, in accordance with the legal requirements for operating a Class 3 invalid carriage in the jurisdiction in which it was sold. Operating the vehicle outside of these limitations may invalidate your warranty.

3 Safety

The Invader should only be operated by a single person, who is not suffering from any condition which impairs vision, hearing, eyesight or the ability to react to sudden changes in surroundings. If you suffer from any of the above, it is recommended that you seek advice from your doctor before operating the Invader.

When operating the Invader please make sure you adhere to the following:

- Always check your mirrors and blind spots when operating through trails.
- Turn on headlights when in need of additional visibility.
- Make sure that your battery power is sufficient before you go out to ride.
- Do not ride with more than 1 occupant.
- Do not over charge the battery by leaving the charger in the charging port.
- Once the battery is fully charged remove the charger immediately.
- Do not try to operate the unit while charging.
- Do not let anyone under the age of 16 years old operate this vehicle.
- To avoid tipping, do not operate this unit up extreme inclines.
- To avoid tipping, do not make sharp / abrupt turns at high speeds.
- Do not operate under the influence of any use of drugs or alcohol.
- Do not operate at excessive speeds.
- Do not completely submerge the unit in water.

3.1 Safe Inclines

The Invader can climb inclines of up to 14° without danger. On this 14° incline, the Invader can stop, brake and turn.




Figure 3 – Recommended inclines

4 Introduction

Your Invader is a high-tech piece of mobility equipment that will give you years of faithful service and enjoyment. This manual introduces you to the operation, maintenance and care of your Invader. If you have any questions, or are unsure of anything, please contact the dealer your originally purchased the Invader from. All maintenance work should be carried out either by an authorised Scooterpac dealer or by a certified mechanic.

5 Your Invader

5.1 Intended Use

The Invader is designed for use off-road including gravel, mud, sand, or snow surfaces as well as on road environments including smooth pavements and roadways, in accordance with local laws. The Invader can be used in wet and windy weather, but discretion should be used when planning a journey in adverse weather conditions. If there is standing water on the pavement, extra care should be taken as the Invader may have reduced ability to grip and steer. Under no circumstances should more than one person operate the vehicle at any one time.

5.2 Unintentional Movement

The Invader should be stationary before use. When the Invader is switched on, it will remain stationary with the manual brake levers engaged and will not move until these are released and the forward or reverse throttle lever is twisted.

Do not attempt to operate from outside the vehicle.

If the vehicle is moving an emergency stop can be performed by releasing the throttle levers and firmly pulling the handoperated brake levers located on the left-hand and right-hand side of the steering handlebar.

6 Exterior Guide



Figure 4 – Exterior guide

1. Mirrors

- 2. Brake Handle
- 3. Turn Signals
- 4. Headlight
- 5. Shocks
- 6. Tires
- 7. Footrests
- 8. Charging Port
- 9. Motor
- 10. Seat Adjust
- 11. Trunk
- 12. Armrest
- 13. Seat
- 14. Throttle
- 15. Ignition
- 16. Digital LCD Display

7 Handlebar Controls Guide



Figure 5 – Left Handlebar



Figure 6 – Right Handlebar

Left Handlebar

- 1. **High Beam / Low Beam** Toggle this switch to choose between a low or high angle of the headlights. The headlight must be on for this to have an effect.
- 2. **Turn Signals** Push this to the left to indicate turning to the left and back into the middle once you are done. Push this to the right if you are turning to the right.
- 3. **Reverse Switch** Press and hold this while engaging the throttle to go in reverse. **Always be aware of your surroundings when operating in reverse.**
- 4. Horn Push this to operate the horn.

Right Handlebar

- 1. **Front Brake** Pull this lever to engage the front brake. Use the rear brake first located on the left handlebar.
- 2. Throttle Slowly rotate this towards you to engage the motor.
- 3. All Wheel Drive Selection Switch In the right position this switch will enable AWD mode (both front and rear motors). In the left position this switch will enable RWD mode (rear motor driving).
- 4. **Lights** Push this to the left most position to turn on dipped beam. Push this to the middle position to have the side lights on. Push the switch all the way to the right to turn off all lights.
- 3 Speed Switch Use this switch to choose between 4mph (Pavement) and 8mph (Road). Position 1 equals 4mph and position 2 equals is 8mph. Please note – position 3 is not in use and If switched to position 3, the Invader will be set to position 2.

8 Operating Your Invader

8.1 Getting Started

Before use, ensure that the Invader is stationary on smooth, level ground. Only operate when you are safely and comfortably seated.

8.2 Keys & Fobs

The Invader is delivered with several keys which operate various functions:




Figure 8 – Alarm Fob

Alarm Fob Guide

- 1. **Lock Button** Press this button to arm the alarm. The alarm will not engage until 5 seconds after you arm it. Press this button once you have finished riding it.
- 2. **Unlock Button** Press this button to disable the alarm. Press this before riding your Invader.
- 3. **Panic Button** Press this button to set off the alarm. Use this in case of emergencies or to locate your vehicle.
- 4. **Remote Start** Press this twice to start the Invader without using the keys. Press the unlock alarm button (2) to disengage the remote start.


8.3 Seat Adjustments

It is important to adjust the seat into a good position that allows you to comfortably operate all the vehicle controls.

Forward/Backwards

To move the seat forwards or backwards, grasp the black lever on the righthand side underneath the seat whilst sitting down.





8.4 Footrests

The Invader is fitted with extendable footrests so you can choose your riding style.

Using your feet push the footrests towards the Invader and they will pop out.

Reversing this process will fold them back into the sides of the Invader.



Figure 10 – Ignition barrel

8.5 Ignition

8.5.1 Turning On

Below the front display you will find the ignition barrel.

- 1. Turn the key to position 1 to turn the Invader on. The key cannot be removed while it is in the on position.
- 2. Turn the key to position 2 to turn the unit off.
- 3. Turn the key to position 3 to engage the steering lock. For more information on how to engage the steering lock please read below.

Do not turn the unit on until you are properly seated on the Invader.

8.5.2 Steering Lock

As an added level of protection, the Invader comes with a steering column lock that prevents the wheel from turning to prevent theft. To engage the steering lock you must do the following:

- 1. Turn the handlebars so they are pointing to the left (as if you were sitting on the machine)
- 2. Put the key into the position 2 (see fig. 10) and push down while turning counterclockwise.
- 3. Once it is in position 3 (see fig. 10) remove the key and reverse this process to disengage the steering lock.



Figure 11 – Ignition barrel

8.6 Acceleration & Braking

8.6.1 Accelerating

On the right handlebar is a throttle that must be rotated towards you (bring the back of your hand towards your body) The throttle is very sensitive so be sure to turn it slowly. Make sure that you are on the unit and can easily turn on the brakes.

8.6.1.1 Braking

The acceleration is controlled by the throttle lever and deacceleration is controlled by a front and rear hydraulic disc braking system that allows you to stop effectively.

To activate the brakes, pull the left brake handle which controls the rear brakes and the right handle which controls the front brakes.

PLEASE NOTE Always use the rear braking first before applying the front brake to avoid injury.

To slow down, release the throttle lever and the Invader will decrease speed. The hydraulic disc braking system can be activated by pulling the brake levers located on the left and right side of the handlebars.



Figure 12 – Throttle lever



Figure 13 – Brake lever

8.6.2 Engaging the Brake Lock

The Invader has a brake lock that will prevent it from rolling even when parking the unit on a hill. To engage the brake lock follow the below:

- 1. Pull the brake lever on the left-hand side towards you as much as you can.
- 2. Take the latch with your other hand or other finger and pull it into the grooves of the brake lever.
- 3. Release brake lever and make sure the brakes are stuck in a pressed position.

To disengage the brake lock, just pull the brake lever towards you slightly more and the brake lock latch will pop out. Release the brake lever and you are ready to go!

8.6.3 Reversing

Hold down the green button on the left handlebar (see fig. 5) whilst gently twisting the throttle lever (see fig. 12). This will engage the reversing mode.








Figure 15 – Brake lock




Figure 16 – Brake lock

To engage reverse mode, ensure that the Invader is stationary on even ground. Before moving, check that the area is clear of obstructions and your planned path is of adequate size. Check the wing mirrors prior to manoeuvres.

The wing mirrors fitted to the Invader are large, giving improved visibility and safety. They can be adjusted by gently twisting the housing.

8.7 Digital LCD Display



- Speed This digital reading is a visual representation of how fast you are travelling in km/h.
- 2. **Gear/Speed Mode** To adjust the speed mode please refer to Right Handlebar, figure 6 on page.
- 3. **Odometer** On ignition, this shows how many cumulative kilometres you have travelled overall on your Invader for five seconds. After which it changes to a journey tripmeter, measuring the distance travelled since starting. This resets each time you turn the vehicle off.
- 4. **Battery Meter** This shows how much power you have left before you need to charge. Once your charge is below two white bars recommending charging.

PLEASE NOTE The battery meter will dip down when the Invader is in motion. The metre will return to the previous position when becoming stationary. This is normal.

8.8 Lights

The Invader is supplied with high quality LED headlights that can be activated from the handlebar controls.

To switch on the lights, see fig. 5. When the ignition is switched on the lights are always active – you have a choice between low beam and high beam. It is advisable to use the headlights whenever the Invader is in motion. This will aid other drivers and pedestrians, ensuring you remain safe and seen.

The Invader is fitted as standard with integrated rear brake lights. These brake lights will illuminate when brake levers are engaged.

8.9 Indicators

The indicators are bright LEDs used for easy visibility, in an orange colour.

To activate your indicators, use the switch on the left handlebar (see fig. 5) before initiating a manoeuvre. Once the turn is complete and it is safe to do so, move the switch back to the central position to turn off the indicator.

8.10 Follow-Me-Home Lights

The Follow-Me-Home Lights are a standard safety feature which help to ensure smooth and safe exit in the dark by increasing visibility around the Invader. They can simply be operated by turning the headlights on and then turning the ignition off, the lights will remain on for 10 seconds and then will automatically turn off.

8.11 Horn

The electric horn is activated by pressing the **box** button on the left handlebar (fig. 5). The horn should only be used in compliance with the Highway Code. The horn will only sound if the ignition is switched on.

8.12 Charging the Invader

After using your Invader it will need to be recharged. The Invader is supplied with a charger that can be plugged into a regular 3-pin power socket outlet. The charging port on the Invader is located under the seat, between where your legs would rest.

When the charger is plugged in the wall and not into the Invader the light will appear green. To begin charging, plug the charger into the Invader's charging port (see fig 17). The charger LED will turn red.

After the Invader is fully charged the LED on the charger will turn green. You can unplug this from the Invader. You can charge the unit at any point of its usage. The Invader does not need to be fully discharged before charging again. From low voltage to full the Invader can take between 8-10 hours to fully charge.



Figure 18 – Charging port

PLEASE NOTE – When using off-road, to ensure maximum battery performance, we highly recommended the speed override switch is turned on.

PLEASE NOTE – Do not leave the charger plugged in for extended periods of time after it is finished as it will ruin the battery life and can possibly become a fire hazard.

PLEASE NOTE – For best practice, please ensure to charge your batteries after each use. Do not overcharge your batteries, the charger should be connected for no more than 12 hours continuously. If there are long periods where you decide not to use your scooter, we recommend that batteries are charged at least once a week. This will ensure they remain healthy and are ready for regular usage.

9 Maintenance

9.1 Replacing Bulbs

LEDs are energy efficient and long lasting however they may eventually require replacement. LED bulbs can be purchased from the dealer that supplied your Invader. Replacing bulbs should only be completed by a certified Scooterpac dealer, as it involves disassembling units that must be resealed to the original manufacturing specification.

9.2 Battery Care

The battery assembly in your Invader should not require any maintenance on a day-to-day basis, however access may be required. The batteries are located under the floorpan, protected by a black metal chequered plate.

To access the batteries, the floorpan must be removed. This can be done by undoing four bolts holding it down on each corner.

Once the maintenance has been completed, ensure that all four bolts are used to replace the floorpan securely without crushing or bending any wires.

9.3 Isolation Switches

Behind the seat you will find two bolts that lock the seat rest to the machine. Using an Allen Key, unscrew the two bolts seen below and lift the bar up to access the under-seat compartment.

PLEASE NOTE This is area is not meant to be used for storage.

To prevent surges that may damage the unit, the Invader comes with two isolation switches. This is located underneath the seat just above the controller. In the event of a surge the isolation switches will trigger and turn the whole unit off.

If the Invader does not turn on and the display does not light up when the key is in the ignition, it is most likely that the isolation switches are set to off. Open the seat lock and switch the isolators to the on positions.



Figure 19 – Circuit breaker

9.4 Tyre Pressures

The tyres on the Invader are designed to give a good balance between comfort and grip. Incorrectly inflated tyres may lead to poor handling, reduced range and increased wear. The tyres should always have at least 3mm of tread to provide adequate grip on the road surface. If the tyres become worn, they should be replaced before the Invader is used again.

Front tyre pressure: 10psi Rear tyre pressure: 10psi

9.5 Troubleshooting

- Whenever you get off your Invader activate the brake lock. This will prevent it from rolling away downhill and will also stop someone from accidentally engaging the motor while off the vehicle.
- When engaging the throttle always start slowly to get a feel of how quickly you may move. When braking, use your rear brakes first, and then your front brakes to ensure complete safety.
- An additional lock is advised when leaving it outside for extended periods of time. Secure a safe lock to the frame to prevent theft.
- If the display does not turn on at all when you put the key in the ignition check the breaker switch underneath the seat to see if it is set to "ON".
- If the machine turns on (display etc.) however the motor does not run, make sure the brake lock is not on. The motor will not engage as long as any brake is being pressed.

9.6 Maintenance

- Always ensure that your tyre pressure is set to the recommended pressures.
- Check your brakes before operating, making sure they are firm and the Invader does not move while they are being pulled.
- Check that all lights are working; headlights, brake lights and signal lights.
- When storing the Invader outside, use a cover to prevent weather damage. If possible, store inside otherwise. If possible, bring the battery inside.
- Ensure your Invader undergoes a yearly service and safety check at your local Scooterpac dealer.
- Do not overcharge the battery once the battery is fully charged, unplug it as soon as possible.

9.6.1 Cleaning

9.6.1.1 Seat

The seat should be wiped with a soft dry cloth. Do not use abrasive cleaning materials, and do not use bleach. To restore the deep black colour a vinyl cleaning spray may be used.

9.6.1.2 Paintwork

To care for the paint, regularly wash the Invader using soft cloths and a mild automotive detergent. Apply automotive polish to achieve a high-shine finish. It is highly recommended that polish is applied in areas where the paintwork may be exposed to adverse weather conditions. Failure to keep your Invader clean may lead to corrosion.

TOP TIP – Never use boiling water to clean the Invader.

10 Warranty

The Invader comes with a one-year manufacturer's warranty when purchased new from an authorised Scooterpac retailer. To ensure validity, the Warranty must be registered to Scooterpac within 14 days of purchase.

10.1 One-Year Warranty

From one year from the date of delivery, Scooterpac will provide a warranty on the motor, controller, electronics, and mechanical components.

10.2 Warranty Exclusions

- 1. Seat cushions, including damage caused by fabric cleaning.
- 2. Repairs and/or modifications made to any part of the Invader without the specific and prior consent from Scooterpac.
- 3. Circumstances beyond the control of Scooterpac
- 4. Exclusions also include components with damage caused by:
 - a. Contamination (rain, etc.)
 - b. Abuse, misuse, accident or negligence.
 - c. Commercial use
 - d. Improper operation, maintenance or storage.

10.3 Warranty Policy

The warranty only covers failures due to defects in materials or workmanship which occur during normal use. The warranty is available to the original purchaser and is non-transferable.

The warranty does not extend to the consequential costs resulting from fault clearance, freight and travel costs, loss of earnings, expenses, etc. The manufacturer will not accept responsibility for any damage or injury caused by misuse or non-observation of the instructions set out in this user manual.

11 Specifications

11.1 Technical Specification

Motor	Front & Rear Wheel Drive Front Motor – 1500W Rear Motor – 1200W Peak Output – 2700W	Batteries	60V 32Ah SLA
Battery Charger	60V 4 Amp Off-Board Charger	Speed	4mph, 8mph
Dashboard	Digital LCD Display Speedometer Odometer	Locking	Alarm System Manual Steering Locking
Tyres		Pneu	matic

11.2 Sizes & Weights

Class	3 (Invalid Carriage)
Range ¹	30 miles
Brakes	Dual Hydraulic Disc Brakes
Weight Capacity	150 kg / 24 stone
Ground Clearance ^{2,3}	170 mm (unloaded)
Height ²	1150 mm
Length ²	2000 mm
Width ²	845 mm
Tyres	Front - 21" x 7" x 10"
	Rear - 23" x 7" x 10"
Maximum Slope ³	14 degrees / 25%
Seat Back Height	340 mm
Seat Width	475 mm

¹ Range may vary with battery charge/condition/option, terrain type, tyre condition and vehicle loading.

² Due to manufacturing tolerances and continuous product improvement this specification can be subject to variance of +/-3%.

³ Varies with user weight, terrain type, battery charge, battery condition, tyre condition.

12 Servicing

In order to ensure continued safe operation, the Invader must be serviced every 12 months. We recommend recording the servicing dates and locations on the sheets below. Always have your Invader serviced at an authorised Scooterpac dealer, using original Scooterpac parts.

Year	Service		Next Service Due
	Dealer Name	Scooter Shop Ltd	
	Technician Name	David Horton	
	Date of service	01,01,2025	
	Mileage	275 miles	
Sample	Notes	Tested batteries Tested front and rear tyre pressures Checked front and rear lights Checked electronic switches	01,01,2026
	Signed	David Horton	

Year	Service	Next Service Due
	Dealer Name	
	Technician Name	
	Date of service	
	Mileage	
Year One	Notes	
	Signed	
Year	Service	Next Service Due
	Dealer Name	
	Technician Name	
	Date of service	
	Mileage	
Year Two	Notes	
	Signed	

Year	Service	Next Service Due
	Dealer Name	
	Technician Name	
	Date of service	
U	Mileage	
Year Three	Notes	
	Signed	
Year	Service	Next Service Due
	Dealer Name	
	Technician Name	
	Date of service	
<u> </u>	Mileage	
Year Four	Notes	
	Signed	

Year	Service	Next Service Due
	Dealer Name	
	Technician Name	
	Date of service	
	Mileage	
Year Five	Notes	
	Signed	
Year	Service	Next Service Due
	Dealer Name	
	Technician Name	
	Date of service	
	Mileage	
Year Six	Notes	
	Signed	

13 Notes



Tel: 0330 124 1733 E-mail: info@scooterpac.com Web: www.scooterpac.com