

ACCESSORY RANGE FOR HIGH-PRESSURE CLEANERS

FOAMING INJECTOR LANCES / CLEANING AGENTS



NEW!



NEW!



Foaming injector lances - threaded fitting			
Operating pressure max. bar / MPa		250 / 25	
Temperature max. °C		30	
Weight (unfilled) kg	0.34	0.38	
Inlet	M22x1,5 male		
Nozzle size	03		
Container liter	1	2	

Foaming injector lances - quick-release fitting			
Operating pressure max. bar / MPa		250 / 25	
Temperature max. °C		30	
Weight (unfilled) kg	0.35	0.39	
Inlet	Quick release insert D12		
Nozzle size	03		
Container liter	1	2	

Cleaning agent injector kit		
Inlet	M22x1,5 male	
Nozzle size	028	042
<ul style="list-style-type: none"> ■ Incl. stainless steel lance with regulating nozzle ■ For low pressure dispensing of cleaning agents 		
Ord.no.	133767	133766

- with threaded connection
- Production of highly effective foam.

Ord.no. 135301 135311

- with quick-release fitting
- Production of highly effective foam.

Ord.no. 135303 135313



Fig. Foam injectors with threaded fitting



Universal cleaner Alfa Neutral			
pH value**	10.9		
Container Liter	5	25	
<ul style="list-style-type: none"> ■ Universal cleaner for removal of strong contaminations 			
Ord.no.	412589	412588	

Foam cleaner Alfa Plus			
pH value**	13.2		
Container Liter	5	25	
<ul style="list-style-type: none"> ■ Special cleaner to degrease and clean 			
Ord.no.	412700	412709	

Special cleaner Alfa Marine			
pH value**	13.5		
Container Liter	5	25	
<ul style="list-style-type: none"> ■ for cleaning motors ■ specifically for restoration after fire damage ■ Alkaline, can be diluted with water 			
Ord.no.	412584	412583	

Decalcifying (concentrate)			
pH value**	1.0		
Container Liter	1	12 x 1	
<ul style="list-style-type: none"> ■ Descaling of hot and cold water high-pressure cleaners ■ Removal of lime deposits 			
Ord.no.	412580	412570	

Important note:

When using chemical cleaning agents, observe the respective regulations, provisions, safety notes and safety data sheets.

**pH value: Undiluted

We recommend testing the cleaning agent on the surface to be cleaned before starting.

Please indicate the technical data of the high-pressure cleaner when placing your order.