

# KILTER II

6W | 375 lm | 2200K

T30-640-6W-2200K-S14D-FR

Kilter bulb 640mm length 6W 2200K S14D frosted 240V

tala®

The Kilter bulb by Tala is a new take on an architectural lighting staple. Defined by its tubular shape, Kilter achieves consistent light throw and reduce shadowed endpoints while offering Tala's signature dimming characteristics.



## PHYSICAL

Bulb diameter:	30mm
Bulb length:	640mm
Glass shape:	T30
Base:	S14D
Materials:	Glass & nickel
Glass finish:	Frosted
Weight:	195g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54

## ELECTRICAL

Power:	6W
Current:	0.03A
Voltage:	220-240V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	63
Lifetime:	15,000 hrs

## ILLUMINATION

CCT:	2200K
Lumens:	375 lm
Incandescent equiv.:	32W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	75
TM30 - Rg	97
TM30 - Rf	94

IES/LDT photometry files  
and product photography  
available on request



## DIMMING

Dimmable 0-100%  
Recommended dimmer: Varilight V-Pro  
(For a full list of recommended and  
compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,  
London, E2 9DG, United Kingdom

Tala Europe B.V. Bertus Aafjeshove 40  
Nieuwegein 3437 JN

## LOGISTICAL

Unit Packaging  
PC/Ctn: 1  
Gross weight: 600g  
L 700 x W 70 x H 70mm

Outer Carton  
PC/Ctn: 4  
Gross weight: 1.9kg  
L 705 x W 290 x H 75cm

tala.co.uk | hello@tala.co.uk | +44 7700 170343

Specification subject to change without  
notice. Refer to our website for the most  
recent product documentation. Tala  
designs in the EU/UK are protected by  
registered and or unregistered design rights

## WARRANTY

2 years

## EAN

5060915712097

# KILTER II

6W | 375 lm | 2700K

T30-640-6W-2700K-S14D-FR

Kilter bulb 640mm length 6W 2700K S14D frosted 240V

tala®

The Kilter bulb by Tala is a new take on an architectural lighting staple. Defined by its tubular shape, Kilter achieves consistent light throw and reduce shadowed endpoints while offering Tala's signature dimming characteristics.



## PHYSICAL

Bulb diameter:	30mm
Bulb length:	640mm
Glass shape:	T30
Base:	S14D
Materials:	Glass & nickel
Glass finish:	Frosted
Weight:	195g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54

## ELECTRICAL

Power:	6W
Current:	0.03A
Voltage:	220-240V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	63
Lifetime:	15,000 hrs

## ILLUMINATION

CCT:	2700K
Lumens:	375 lm
Incandescent equiv.:	32W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	75
TM30 - Rg	95
TM30 - Rf	92

IES/LDT photometry files  
and product photography  
available on request



## DIMMING

Dimmable 0-100%  
Recommended dimmer: Varilight V-Pro  
(For a full list of recommended and  
compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,  
London, E2 9DG, United Kingdom

Tala Europe B.V. Bertus Aafjeshove 40  
Nieuwegein 3437 JN

## LOGISTICAL

Unit Packaging  
PC/Ctn: 1  
Gross weight: 600g  
L 700 x W 70 x H 70mm

Outer Carton  
PC/Ctn: 4  
Gross weight: 1.9kg  
L 705 x W 290 x H 75cm

tala.co.uk | hello@tala.co.uk | +44 7700 170343

Specification subject to change without  
notice. Refer to our website for the most  
recent product documentation. Tala  
designs in the EU/UK are protected by  
registered and or unregistered design rights

## WARRANTY

2 years

## EAN

5060915712110