

| Feature                   | Godox LITEMONS LA600R (RGB)                                                  | Aputure LS 600d Pro (Daylight)                                                   | Nanlite Forza 500B II (Bi-color)                                | Nanlux Evoke 600 (Daylight)                              | Aputure Amaran 200x (Bi-color)                               | Aputure Amaran 300c (Bi-color)                                          | Neewer AS600B COB LED (Bi-color)                                      |
|---------------------------|------------------------------------------------------------------------------|----------------------------------------------------------------------------------|-----------------------------------------------------------------|----------------------------------------------------------|--------------------------------------------------------------|-------------------------------------------------------------------------|-----------------------------------------------------------------------|
| Price (GBP)               | £800–£900                                                                    | £1,850                                                                           | £1,423                                                          | £2,000–£2,500                                            | £344                                                         | £544.80                                                                 | £1,138.99                                                             |
| Color Temperature Range   | 1800K–10,000K (RGB & Bi-Color)                                               | 5600K (fixed)                                                                    | 2700K–6500K (Bi-color)                                          | 5600K (fixed)                                            | 2700K–6500K (Bi-color)                                       | 2700K–6500K (Bi-color)                                                  | 3200K–5600K (Bi-color)                                                |
| Power Output              | 600W, ~141,000 lux @1m                                                       | 600W, ~98,500 lux @1m                                                            | 500W, ~67,320 lux @1m                                           | 600W, ~166,000 lux @1m                                   | 200W, ~45,400 lux @1m                                        | 300W, ~52,000 lux @1m                                                   | 600W, ~58,000 lux @1m                                                 |
| Color Modes               | Full RGBWW, 14 FX                                                            | Daylight Only, 8 FX                                                              | Bi-color, 11 FX                                                 | Daylight Only, FX modes                                  | Bi-color, 9 FX                                               | Bi-color, 10 FX                                                         | Bi-color, No FX                                                       |
| Color Accuracy (CRI/TLCI) | CRI 95, TLCI 95                                                              | CRI 96, TLCI 96                                                                  | CRI 96, TLCI 97                                                 | CRI ~96, TLCI ~97                                        | CRI 95+, TLCI 98+                                            | CRI 95+, TLCI 98+                                                       | CRI 96+, TLCI 96                                                      |
| Control Options           | Onboard, DMX, App, Optional CRMX                                             | Onboard, Sidus Link, LumenRadio CRMX                                             | Onboard, Nanlink app, DMX                                       | Onboard, DMX, Nanlink app                                | Onboard, Sidus Link app                                      | Onboard, Sidus Link app                                                 | Onboard, 2.4GHz wireless remote                                       |
| Mounting Compatibility    | Bowens S-Type                                                                | Bowens S mount                                                                   | Bowens S mount                                                  | Nanlux NL Mount (Bowens adapter available)               | Bowens S mount                                               | Bowens S mount                                                          | Bowens S mount                                                        |
| Cooling System            | Active cooling (Auto/Medium/High)                                            | Active cooling (internal fan)                                                    | Active cooling (fan)                                            | Active cooling (fan)                                     | Active cooling (quiet)                                       | Active cooling (quiet)                                                  | Active cooling (fan)                                                  |
| Power Supply              | AC 100–240V, DC 48V XLR                                                      | AC 100–240V (V-mount option)                                                     | AC 100–240V (V-mount option)                                    | AC 100–240V (48V input option)                           | AC 100–240V (DC adapter optional)                            | AC 100–240V (DC adapter optional)                                       | AC 100–240V (V-mount compatible)                                      |
| Included Accessories      | Reflector, AC adapter, padded case                                           | Hyper Reflector (55°), Control Box, 3m head cable, rolling case                  | Reflector (55°), Control Box, Clamp, 3m head cable, padded bag  | Reflector (45°), Ballast, Cables, Hard case              | Hyper Reflector, AC adapter, Bowens modifiers                | Hyper Reflector, AC adapter, Bowens modifiers                           | Reflector, AC adapter, light stand                                    |
| Special Features / USP    | Full RGB flexibility, Green/Magenta adjustment, App control, NFC tap-to-pair | High output, Weather-resistant, Battery charging feature, Sidus Link app control | Next-gen bi-color, Fanless ballast (silent), Lightweight design | Cine-grade brightness, Weather-proof, Professional build | Affordable, Sidus Link integration, Lightweight, Easy to use | Compact and powerful, Sidus Link integration, Suitable for small spaces | Affordable, Powerful output for the price, Suitable for studio setups |
| Special Effects (Number)  | 14                                                                           | 8                                                                                | 11                                                              | 5                                                        | 9                                                            | 10                                                                      | 0                                                                     |