

LED DOWNLIGHT RANGE

# Evoque

Elevate Every Space



Crompton Greaves Consumer Electricals Limited  
05GBD, Godrej Business District, Pirojshanagar,  
Vikhroli (West), Mumbai, Maharashtra - 400079, India  
Customer Care No. : +91 9228880505 | [www.crompton.co.in](http://www.crompton.co.in)  
Email: [consumer.support@crompton.co.in](mailto:consumer.support@crompton.co.in)



Every space start as a vision.  
A vision of creativity –  
where design defines performance...  
and lighting is crafted for the people.

# Evoque

...lights up your vision;  
elevating every nook and corner  
with lighting that speaks for itself.

Evoque is engineered to deliver unmatched efficiency, aesthetic appeal, and long-lasting reliability to your space. Be it an office space, retail showroom or a hospitality setup, Evoque adapt seamlessly to the requirement of every setting, efficiently illuminating the space without compromises.

## Design flexibility that match every vision



Available with  
deep inset or flush  
diffuser in  
standard or  
prismatic lens

Offers aesthetic  
choices from  
round & square  
recessed to  
square flush  
diffuser

Flexible  
installation  
possibilities with  
recessed and  
surface mounting  
designs

## Light that adapts to mood and purpose

Evoque is tailors lighting,  
creating warm, welcoming  
spaces or cool, productive  
environments, according to the  
atmosphere you want.



High efficiency LEDs  
with a wide range of  
system efficacies



Housed in a sleek, sturdy  
& white housing blending  
seamlessly into interiors



**K** Available in a wide  
range of wattages and  
CCTs to suit the space  
requirement





# Technical Specifications



**Housing**  
Pressure Die-cast  
Aluminium



**Diffuser**  
Standard and  
Prismatic



**Wattages**  
6W to 30W



**Burning Hours**  
> 50,000



**Efficacy**  
110 / 125 / 140 Lm/W



**CCT**  
4000K / 5700K / 6500K



**I THD**  
< 10%



**Mounting System**  
Recessed and Surface



**Surge**  
4kV



**Protection**  
IP40



**P.F.**  
> 0.95

## 120mm Diameter Flush Recess Type

|                                 | Wattage (W) | CRI | Mains Current (A) | Approx. Wt. (Kg) | CCT(K)    |
|---------------------------------|-------------|-----|-------------------|------------------|-----------|
| <b>TDR-305-06-57-HL1-DP-NWH</b> | 06          | 80  | 0.027             | 0.180            | 5700 ANSI |
| <b>CDR-305-06-57-HL1-DP-NWH</b> | 06          | 80  | 0.027             | 0.180            | 5700 ANSI |

- Available wattages 6W / 9W / 12W  
Replace 06 with 09 / 12 in the above catalogue reference number
  - Available in 4000 / 5700 / 6500 CCT  
Replace 57 with 40 / 65 in the above catalogue reference number
  - Required mains current  
6W – 0.027A / 9W – 0.040A / 12W – 0.053A
- \*\*RATED SYSTEM WATTAGE AND CURRENT WILL HAVE TOLERANCE AS PER IS 16104: 2012

For Suspended Version

**TCR-305-06-57-HL1-DP-NWH**

For Recess Version

**CDR-305-06-57-HL1-DP-NWH**

