



Stronghold® 60

High Pressure Couplings

Product Description

The Stronghold 60 range of couplings and plugs are made to the TEMA style quick release coupling, used as industry standard on all leading high pressure cleaning systems. The principle of the design is a 'straight through' fluid path causing minimal turbulence, so that fluid flow rates are kept to an optimum. The unique design saves dirt ingress and grease loss, increasing the life of the couplings.

Features

- Robust Mild Steel, Plated Brass or Stainless Steel construction.
- Industry Standard coupling system type.
- Ease of operation.
- High grade Stainless Steel Version available.
- Unique design for greater Hygiene and Longevity.
- 10 Ball Bearing design for positive connection and long life.

Technical Details

- Max System Pressure: 350 Bar
- Max System Temperature: 90°C
- Rated Burst Pressure: 1200 Bar
- Rated temperature range: -30°C – 100°C

N.B.: Rated pressure and temperature ranges refer to the coupling only, and not to the complete hose, lance, gun or other assembly. Rated pressure and temperature in this case is dependent on the installation or clamping method used.

- Material: 316 Stainless Steel, Mild Steel or Passivated Brass.
- Flow Path: 3/8"



Ordering Details

Stronghold 60 Coupling. Stainless Steel. 3/8 Fm	1620
Stronghold 60 Coupling. Plated Brass. 3/8 Fm	0615
Stronghold 60 Plug. Stainless Steel. 3/8 Fm	1621
Stronghold 60 Plug. Mild Steel. 3/8 Fm	0616