

PiXAPRO®

RAPIDSTAND™ 225

CLICK-OPEN PORTABLE LIGHT STAND

*Patented Design



Automatic Deployment



Air Cushioned



5kg Max. Load



Removeable Spigot



71cm Folded Length

QUICK START GUIDE

1 Folded Position



Stand in folded position

2 Press Foot Release Button



Press the foot to release to button at the base

3 Legs Automatically Deploy



The legs will automatically deploy outward

4 Red Locking Collar



Rotate the collar to the "LOCK" position before use

5 Mount Equipment



Mount your light, camera, or accessory using the spigot

6 Adjust Height



Loosen the locking clamps to extend the stand to the desired height, then tighten

INTERCHANGEABLE SPIGOT

DUAL 1/4"-20 & 3/8"-16 THREAD

Includes a reversible spigot for maximum Compatibility



COMPATIBLE EQUIPMENT

Suitable for Flash heads, LED light fixtures, and other studio accessories



FOLDED POSITION

Folds compact, and comes with a carry bag for easy transportation



TECHNICAL SPECIFICATIONS

Model	RAPIDSTAND 225
Max. Height	225cm
Min. Height	75cm
Folded Length	71 cm
Folded Diameter	52mm
Net. Weight	1.56kg
Max. Load	5kg (@225cm height)
Pole Diameter	25/28/32/36mm
Leg. Diameter	43mm
Footprint	100cm
Air-Cushioned	Yes
Removable Spigot	Yes
Spigot Thread	1/4"-20 & 3/8"-16
Material	Aluminium Alloy

SAFETY INFORMATION

- ⚠ Always deploy on a firm flat level surface.
- ⚠ Ensure locking collar is fully locked before mounting equipment.
- ⚠ Do NOT exceed the max. load capacity of 5kg
- ⚠ Remove equipment before folding or transporting the stand
- ⚠ Keep hands and fingers clear of moving parts during deployment and folding
- ⚠ Use additional ballast or sandbags when used in windy conditions.
- ⚠ Inspect the stand regularly for damage or loose parts before use
- ⚠ Do NOT use if any part of the stand is damaged
- ⚠ Keep out of reach of children

WHAT'S INCLUDED



- 1x RAPIDSTAND 225
- 1x Carry Bag
- 1x Spigot
- 1x User Manual