

HOT WATER – OIL HEATED  
**The therm CA-Series**



**Integrated Hose drum**

Practical design and features a longer length high-pressure hose complete with folding crank (Version incl. hose drum)

**Operating panel arranged for good overview**

with adjustable rotary thermostat for controlling the water temperature

**Removable covers**

Protect the mechanical components from environmental factors and provide convenient access

**Cleaning Agent Intake**

Injector system for dispensing of cleaning agents

**Pressure regulation**

Fully adjustable control allows operating pressures to be set to suit any task

**Parking brake**

For a secure stationary position

Figures: therm CA 12/150 incl. hose drum



Technical specifications	therm CA 11/130		therm CA 11/130		therm CA 12/150		therm CA 12/150		therm CA 15/120		therm CA 15/120	
	without hose drum		incl. hose drum		without hose drum		incl. hose drum		without hose drum		incl. hose drum	
Operating pressure adjustable	bar / MPa		30-130 / 3-13		30-130 / 3-13		30-150 / 3-15		30-150 / 3-15		30-120 / 3-12	
Max. admissible overpressure	bar / MPa		145 / 14.5		145 / 14.5		165 / 16.5		165 / 16.5		135 / 13.5	
Connected load	V / ~ / Hz / A		230 / 1 / 50 / 15		230 / 1 / 50 / 15		400 / 3 / 50 / 7.2		400 / 3 / 50 / 7.2		400 / 3 / 50 / 7.2	
Motor speed	Rpm		1400		1400		1400		1400		1400	
Water output	l/min l/h		11	660	11	660	12	720	12	720	15	900
Power intake / Power output	kW kW		3.4	2.3	3.4	2.3	3.8	3.0	3.8	3.0	3.8	3.0
Volume water tank	l		4		4		4		4		4	
Hot water output adjustable	°C		12-82		12-82		12-80		12-80		12-80	
Steam level	°C		140		140		140		140		150	
Heating output	kW		55		55		58		58		65	
Fuel tank	l		25		25		25		25		25	
Power supply cable	m		5		5		7.5		7.5		7.5	
Dimensions L x W x H	mm		860 / 580 / 970		860 / 580 / 1220		860 / 580 / 970		860 / 580 / 1220		860 / 580 / 970	
Weight	kg		150		171		150		171		181	
Cleaning Agent Intake			●		●		●		●		●	
<b>Equipment</b>												
Hose drum			-		●		-		●		-	
Steel braided high-pressure hose	m		10		15		10		15		10	
Trigger gun with safety catch	Model		M2000		M2000		M2000		M2000		M2000	
Stainless steel lance with flat jet nozzle	Nozzle size		● D25045		● D25045		● D25045		● D25045		● D2507	
<b>Ord.no.</b>			<b>414606</b>		<b>414607</b>		<b>414616</b>		<b>414617</b>		<b>414626</b>	
											<b>414627</b>	

**EVEN BETTER NOW!**

**MAKING A CHANGE IS EASY**

The therm-CA and therm-C series are now being supplied with a two piece trigger gun with safety catch and lance with threaded fittings.

- Flexible use of Kränzle accessories

More can be found starting on page 49 (Accessories range)



For detailed technical information, see page 84-85