HOT WATER – OIL HEATED

The therm 1-Series







And the second s		therm	1165-1	therm	1165-1
Technical specifications		without hose drum		incl. hose drum	
Operating pressure adjustable	bar / MPa	30-165 / 3-16.5		30-165 / 3-16.5	
Max. admissible overpressure	bar / MPa	180 / 18		180 / 18	
Connected load	V / ~ / Hz / A	400 / 3 / 50 / 12		400 / 3 / 50 / 12	
Motor speed	Rpm	1400		1400	
Water output	l/min l/h	19.4	1165	19.4	1165
Power intake / Power output	kW kW	6.4	5.0	6.4	5.0
Volume water tank	T	4		4	
Hot water output adjustable	°C	12-82		12-82	
Steam level	°C	155		155	
Heating output	kW	78		78	
Fuel tank	I	35		35	
Power supply cable	m	7.5		7.5	
Dimensions L x W x H	mm	1050 / 800 / 1015		1050 / 800 / 1300	
Weight	kg	217		223	
Cleaning Agent Intake		•		•	
Equipment					
Hose drum		-			•
Steel braided high-pressure hose	m	10		20	
Trigger gun with safety catch	Model	Starlet		Starlet	
Stainless steel lance with flat jet nozzle Nozzle size		• D2507		D2507	





Water output > 1000 l/h

For more models from the therm-1 series, see the previous page



g. Non-marking version (NoM). Info on pag

For detailed technical information, see page 87