



**NOTE: TURN POWER OFF AT CIRCUIT BREAKER BEFORE INSTALLING.**

**PRODUCT CONTAINS SHARP EDGES. WEAR GLOVES WHEN INSTALLING.**

1. Remove center brackets by flexing channel outward and tilting brackets out.
2. Install (4) sockets on white wire harness on (2) brackets (A+C) where all 4 sockets face same direction.
3. Same for black brackets B+D
4. **For unit mounting:** Attach ends caps to ends making sure tabs go through slots and stay inside channels - once installed, do not remove. Mount fixture.

**For row mounting:** Insert end cap into slots and install next fixture with no gap between fixtures.

5. **With power off**, ground fixture at green screw, then connect supply wires with wirenuts (black to black, white to white).
6. A. Insert fastener in hole in cover, insert cover tabs into slots, align fastener with hole and turn 90 degrees.  
B. Insert lamp into sockets with AC power towards center sockets and rotate 90 degrees.

#### **PACKAGE INCLUDES:**

1X 8 FT. FIXTURE CHANNEL  
 4X BRACKETS  
 2X END PLATES  
 2X COVERS  
 2X FASTENERS  
 1x WHITE WIRE HARNESS WITH 4 SOCKETS  
 1X BLACK WIRE HARNESS WITH 4 SOCKETS  
 4X LED TUBES  
 ACCESSORY BAG