

15.5K Rooftop unit for Furrion Chill Air Conditioner System

FACR15SA

## FACR15SA-BL



## FACR15SA-PS









EASY INSTAL



HIGH ENERGY EFFICIENCY



AERODYNAMIC DESIGN



PROFILE







UV RESISTANT



LIGHTWEIGHT



VIBRATIONSMART™



CLIMATESMART™





AVAILABLE IN BLACK OR WHITE


- Advanced cooling performance
- Fit for manual and electronic air distribution box
- Dual fans run more efficiently and reduce operating noise
- Cleanable and replaceable air filter


- Available in stylish black and white options
- Fit for ducted or non-ducted cooling systems
- Aerodynamic rooftop design reduces wind resistance
- UV resistant cover, base and rear grill

# FACR15SA | 15.5K ROOFTOP AIR CONDITIONER









Dual Fan Motors

Overload Protection

3 Fan Speeds (High/Med/Low)

Thermo-insulated Heat Exchanger Enclosure

Specifications	
Performance	
Capacity	3760W
EER	2.19
Set Temperature Range	60°F to 86°F/16°C to 30°C
Outdoor Sound Pressure Level	80dB
IP class	IP24
Refrigerant	R410A
Electrical Volts/Frequency/Phase Power (Cooling)	115V/60Hz/1Ph 1720Watts
Amps (Cooling)	15.4
Features	
Eco-friendly Refrigerant	√
Rubber Damper	$\sqrt{}$

## Packaging Information

Packaging Type	Master Carton Box
Quantity Per Box (pcs)	1
Individual Packaging Dimensions (W x H x D)	35½1′16″ x 28½16″ x 15½″ (906 x 722 x 393mm)
Individual Packaging Gross Weight (lbs/kg) Individual Packaging Net Weight (lbs/kg)	90.4 / 41 81.6 / 37
Container Load Information	
20' Container Load (pcs)	120
40' Container Load (pcs)	252
40'HQ Container Load (pcs)	252