




FF34SW15A-BL



FF34SW15A-SS



WORKS WITH
UNIMOTE



VIBRATIONSMART



CLIMATESMART



OVERHEATING
SAFETY CUT-OFF



SLIDE-OUT
SAFETY CUT-OFF



TEMPERATURE
CONTROL SETTINGS



HEAT UP
TO 500sq.ft



SIMULATED WOOD
WITH 4-LEVEL LED
FLAME TECHNOLOGY




TIMER

- Flame effect technology: traditional flame
- 4 flame brightness settings
- Black tempered glass front panel
- LED control board
- Temperature control

- Slide-out safety cut-off: close proximity sensor switches power off automatically
- Adjustable temperature settings from 65°F to 95°F
- Timer setting up to 5 hours
- Remote control included



FF34SW15A | 34" BUILT-IN ELECTRIC FIREPLACE



Specifications

Rated Voltage	AC 120V/60Hz
Heating Output	750W/1500W
LED Control Board	✓
Timer	✓
Log Fuel Effect	✓
Remote Type	IR

Dimensions

Product Size (L x H x W)	33 ⁷ / ₈ " x 17 ³ / ₄ " x 6 ¹ / ₄ " (860 x 450 x 158mm)
--------------------------	--

Packaging Information

Packaging Type	Brown Carton Box
Quantity Per Box (pcs)	1
Individual Packaging Dimensions (L x H x W)	35 ¹¹ / ₁₆ " x 19 ¹ / ₂ " x 8" (905 x 495 x 202mm)
Individual Packaging Gross Weight (kg/lbs)	20/44.1
Individual Packaging Net Weight (kg/lbs)	17/37.5

Box Container Qty

20' - Box Container Qty	300
40' - Box Container Qty	600
40'H - Box Container Qty	680