



WPL4M | Mobile Label Printer **Quick And Reliable Portable Printer With a Ruggedized Design For the Mobile Worker**



Key Features

- Up to 4 inches per second (102 mm) print speed
- 16 MB Flash memory, 32 MB SDRAM
- microSD Flash memory expansion up to 4 GB
- Portable and user-friendly design
- USB 2.0, Bluetooth and 802.11 a/b/g/n Wireless interfaces (depending on the model)
- Label capacity up to 2.5 inches (67.3 mm) OD
- WPL firmware for plug-n-play ease

WPL4M | Mobile Label Printer

RESOLUTION	203 DPI (8 dots/mm)
PRINTING METHOD	Direct Thermal
PRINT SPECS	Max Print Speed: 4 IPS (102 mm per second) 2, 3 IPS for peeler mode Max Print Width: 4.09 in (104 mm) Max Print Length: 90 in (2,286 mm) Max Label Capacity: 2.65 in OD (67.3 mm)
PHYSICAL SPECS	Dimensions: 6.30 in (W) x 7.54 in (H) x 3.11 in (D) / 160 mm (W) x 191.6 mm (H) x 79 mm (D) Weight: 2.43 lbs. (1.1 kg)
PROCESSOR & MEMORY	32-bit RISC CPU; 16 MB Flash memory, 32 MB SDRAM, microSD card reader for Flash memory expansion, up to 4 GB
INTERFACE	USB 2.0, RS-232, Bluetooth (WPL4MB), 802.11 a/b/g/n Wi-Fi (WPL4ML)
POWER	7.2V DC, 5800 mAh Li-ion rechargeable battery
OPERATION	2 buttons (Power, Feed) & 6 LED indicators (Printer, Battery, Wireless status)
SENSORS	Transmissive gap sensor, Black mark reflective sensor, Peel sensor, Head open sensor
INTERNAL FONTS	8 alpha-numeric bitmap fonts, Monotype Imaging® true type font engine with one CG Triumvirate Bold Condensed scalable font
BARCODE	1D bar code: Code 11, Code 39, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN14, EAN128, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, POSTNET, China Post, ITF14, TELPEN, PLANET, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS 2D bar code: Code 49, PDF-417, MicroPDF417, Maxicode, DataMatrix, QR code, Aztec, CODABLOCK F mode, GS1 Databar
PRINTER LANGUAGE	WPL (Compatible to EPL, ZPL, ZPL II), ESC-POS or CPCL emulation
MEDIA TYPE	Continuous, die-cut, black mark, fan-fold, notch (outside wound)
MEDIA SPECS	Width: 2.0 in ~ 4.4 in (50.8 mm ~ 112 mm) Thickness: 2.2 ~ 6.5 mil (0.055 mm ~ 0.165 mm) Core Diameter: .5 in ~ 1 in (12.7 mm ~ 25.4 mm) Label Length: 0.5 in ~ 90 in (12.7 mm ~ 2,286 mm) 1 in ~ 6 in (25.4 ~ 152.4 mm) for peeler mode
ENVIRONMENT	Operation: 14 ~ 122°F (-10 ~ 50°C), 10 ~ 90% non-condensing Storage: -40 ~ 140°F (-40 ~ 60°C), 10 ~ 90% non-condensing
SAFETY	FCC, CE, CB, CCC, TÜV, SRRC, BC, NCC
ENVIRONMENTAL CONCERN	Comply with RoHS, WEEE
INCLUDED	Printer, Belt Clip, Li-ion battery, Power Cord, Power Supply, CD with driver and manual, SDK for iOS (iPhone & iPad), Android 2.2 or higher, WinCE/WM 6.0/6.1pro can be downloaded from website.
WARRANTY	2 Year Limited
ACCESSORIES	Li-ion Battery, Charge Station 1 Cell, IP54-Rated protective case with shoulder strap, Print head for WPL4M



Wasp North America
1400 10th Street
Plano, Texas 75074
1-866-547-9277
www.waspbarcode.com

Wasp Europe
Dunstable Road
Redbourn, St Albans AL3 7PR, UK
0845-430-1971
www.waspbarcode.co.uk

Wasp International
+1 214-547-4100