
## NO.1 PENDANT - TRIO CLUSTER

## Tom Raffield

## **Product Specification**



The No.1 Pendant - Trio Cluster marries form and function. Featuring three sculptural spheres of ash, oak or walnut wood handcrafted from sustainably sourced timber, this cluster ceiling light boasts an intense, captivating aesthetic and is sure to become a unique focal point in your space. Steam bent, hand twisted and assembled into a nest of infinite bends, each individual No.1 Pendant distributes a sculptural mix of light and shadow across your space, wherever you choose to position it.

Locate in a stairwell or hallway for maximum impact or simply suspend at a lower height in a lounge or over a kitchen island to create your very own masterpiece at home.

Our signature pendant lights, your way!

Product Type : Pendant Cluster	SKU	NA (a a el Arres a a	Dimensions L x W x H (mm)		Weight (kg)	
		Wood types	Unboxed	Boxed	Unboxed	Boxed
No.1 Pendant - Trio Cluster Black	TR-NO1-P-A-CLS-BLK	Ash			3.65	10.7
	TR-NO1-P-O-CLS-BLK	Oak				
	TR-NO1-P-W-CLS-BLK	Walnut		470 x 470 x 480		
No.1 Pendant - Trio Cluster White	TR-NO1-P-A-CLS-WHT	Ash		470 x 470 x 480		
	TR-NO1-P-O-CLS-WHT	Oak	470 x 470 x 480			
	TR-NO1-P-W-CLS-WHT	Walnut				
Materials	Ash	Oak	Walnut		Other materials	
					Black or white powder coated metal ceiling plate	
Finish	Non-toxic, hard wearing water based varnish - satin					
Ceiling kit option 1	Black ceiling plate, brass bulb holders and cord grips	Ceiling kit	Flex Flex colour: black fabric Flex length: 2m (Adjustable)		Recomended light bulb	
		Ceiling plate: Ø400mm				
		E27 (240v)			Max 25W LED	
Ceiling kit option 2	White ceiling plate, brushed steel bulb holders and cord grips	Ceiling kit	Flex			
		Ceiling plate: Ø400mm	Flex colour: white fabric Flex length: 2m (Adjustable)			
		E27 (240v)				
Care information	Dusting your light regularly and with a light feather duster should keep your light looking clean, otherwise wipe with a damp cloth and remove any moisture with a dry cloth. Gentle furniture polishes can also be used.					
Additional information	Suitable for use on 240v     Installation instructions of					

This product must be installed by a qualified electrician.