


GRWP10	Cat. #		SELSER™ LIGHTING PRODUCTS
	Job	Type	
			Approvals




5 Year
Warranty



Mounting

0° to +90° tilt adjustments, To meet the needs of customers with different lighting angles.



Housing

Suitable for both indoor and outdoor application, also suitable for J-BOX mounting and surface mounting.



Photocell

Optional for photocell, and allows for security and energy saving






Lens

Polycarbonate optical lens with UV stabilizers do not exhibit yellowing and deformation.

DIMENSIONS




unit: mm/inch

Small size: 27W/40W



Net Weight:
27W: 1.52kg (3.351lb)
40W: 1.80kg (3.968lb)

Medium size: 67W/80W



Net Weight:
67W: 3.32kg (7.319lb)
80W: 3.54kg (7.804lb)




© 2019 Selsler Lighting Products All rights reserved.

Due to our continued efforts to improve our products, product specifications are subject to change without notice. Selsler Lighting Products reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

SELSER™
LIGHTING PRODUCTS

Selsler Lighting Products
Po Box 45160
Baton Rouge, La. 70895
Phone # (225) 412-0025

PHOTOMETRICS



ACCESSORIES



PHOTOCELL

No. PC-JL-120-277V

USE: Photocell is field installed or pre-installed in factory by requesting

PERFORMANCE DATA

		3000K (70CRI)		4000K (70CRI)		5000K (70CRI)	
SYSTEM WATTS	VOLTAGE	LUMENS	LPW	LUMENS	LPW	LUMENS	LPW
27W	120-277VAC	3500lm	130 lm/W	3600lm	133 lm/W	3600lm	133 lm/W
40W	120-277VAC/347-480V	5000lm	125 lm/W	5200lm	130 lm/W	5200lm	130 lm/W
67W	120-277VAC/347-480V	8600lm	128 lm/W	8800lm	131 lm/W	8800lm	131 lm/W
80W	120-277VAC	10000lm	125 lm/W	10500lm	131 lm/W	10500lm	131 lm/W

ELECTRICAL DATA

NUMBER OF DRIVERS	DRIVER CURRENT (mA)	NOMINAL POWER (W)	INPUT VOLTAGE (V)	CURRENT (Amps)
1	430	27	120	0.23
		27	208	0.13
		27	240	0.11
		27	277	0.10
1	640	40	120	0.33
		40	208	0.19
		40	240	0.17
		40	277	0.14
1	1110	67	120	0.56
		67	208	0.32
		67	240	0.28
		67	277	0.24
1	2120	80	120	0.67
		80	208	0.38
		80	240	0.33
		80	277	0.29



© 2019 Selsler Lighting Products All rights reserved.

Due to our continued efforts to improve our products, product specifications are subject to change without notice. Selsler Lighting Products reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

SELSE
LIGHTING PRODUCTS


Selsler Lighting Products
Po Box 45160
Baton Rouge, La. 70895
Phone # (225) 412-0025

Slim wall pack is available in two watts for a variety of applications including building perimeter, entrances, stairways and security lighting. GRWP10 series of luminaries provides a low-profile architectural style with the power of bright, energy efficient LEDs. It has a rugged aluminum construction with multi-mount capabilities. 0° to +90° tilt adjustments. For a building that has a modern or futuristic look.

FEATURES

- » Sealed die-casting profile for outdoor applications
- » Suitable for applications requiring 3G testing prescribed by ANSI C136.31
- » Light engines are available in standard 3000K/4000 K and 5000 K (70 CRI) configurations
- » Scalable Lumen Packages from 3,500 to 10,500 Lumens
- » Tempered UV coated flat lens provide outstanding performance, uniformity and glare control
- » Standard drivers feature electronic universal voltage (120-277V 50/60Hz) operation
- » Greater than 0.9 power factor, less than 20% harmonic distortion, and is suitable for operation in -40°C to 40°C ambient environments
- » Estimated 50,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations
- » Five-year warranty
- » Security, pathway and perimeter lighting, Building entryways and walkways

ORDER MATRIX



FIXTURE TYPE	POWER CONSUMPTION	VOLTAGE	CCT	FINISH	PHOTOCELL (Option)	DIMMABLE	INTERNAL CODE
GRWP10	27 27Watts 40 40Watts 67 67Watts 80 80Watts	27V 120-277V	30K 3000K 40K 4000K 50K 5000K	DB Dark Bronze B Black W White	P0 120-277V Photocell Blank Without Photocell	D 0-10V Blank NON Dimmable	Blank Alphanumeric



© 2019 Selsler Lighting Products All rights reserved.
 Due to our continued efforts to improve our products, product specifications are subject to change without notice. Selsler Lighting Products reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.



Selsler Lighting Products
 Po Box 45160
 Baton Rouge, La. 70895
 Phone # (225) 412-0025