PROFESSIONAL



GIGA X3 A flexible move into the top class





Benefits

- 4.3" touchscreen colour display
- Precision ceramic disc grinder with Automatic Grinder Adjustment (A.G.A.[©])
- Speed function thanks to additional hot water bypass
- 2 thermoblocks and 2 pumps

Recommended accessories

- Glass Cup Warmer
- Cool Control
- Milk Cooler Piccolo
- Smart Payment Box
- Coffee grounds disposal/ drip drain set
- Coffee to Go furniture range

Areas of use

Office floor solutions
Seminar/conference facilities
Breakfast room
Catering
Coffee to Go

Recommended maximum daily output 150 cups

The GIGA X3 allows JURA to impressively demonstrate Swiss innovation and professionalism down to the very last detail. Anywhere where a capacity of up to 150 cups is the order of business, the machine impresses users with its quality, functionality and reliability. Coupled with top performance in every respect, this results in a high-tech automatic coffee machine that is ideally tailored to the requirements of large offices, the breakfast, seminar and conference venue sectors as well as self-service areas.



PROFESSIONAL



GIGA X3

Technical data

Specific advantages	
No. of individually programmable specialities	32
One-Touch function	
Automatic Grinder Adjustment (A.G.A.®)	_ •
Intelligent Water System (I.W.S.®)	_
Speed function	_
Automatic switchover from milk to milk foam	
Compatible with J.O.E.®	
Rotary Switch	
Wireless ready	
Smart Connect supplied as standard	
Power hot water system (3 temperature levels)	0.51/min.
Recognition for second, ground coffee	
Generating code groups	
Active bean monitoring	_
Monitored drip tray	_
Aroma preservation cover	_
Swiss made	
JURA standards	
Pulse Extraction Process (P.E.P.®)	
Pulse Extraction Process (P.E.P.®) Variable VC brewing unit, from 5 g to 16 g	
Pulse Extraction Process (P.E.P.®) Variable VC brewing unit, from 5 g to 16 g	:
Pulse Extraction Process (P.E.P.®) Variable VC brewing unit, from 5 g to 16 g Intelligent Pre-Brew Aroma System (I.P.B.A.S.®)	Electrically adjustable
Pulse Extraction Process (P.E.P.®) Variable VC brewing unit, from 5 g to 16 g Intelligent Pre-Brew Aroma System (I.P.B.A.S.®) Grinder	Electrically adjustable ceramic disc grinder
Pulse Extraction Process (P.E.P.®) Variable VC brewing unit, from 5 g to 16 g Intelligent Pre-Brew Aroma System (I.P.B.A.S.®) Grinder High-performance pump, 15 bar	Electrically adjustable ceramic disc grinder
Pulse Extraction Process (P.E.P.®) Variable VC brewing unit, from 5 g to 16 g Intelligent Pre-Brew Aroma System (I.P.B.A.S.®) Grinder High-performance pump, 15 bar Thermoblock heating system	Electrically adjustable ceramic disc grinder 2
Pulse Extraction Process (P.E.P.®) Variable VC brewing unit, from 5 g to 16 g Intelligent Pre-Brew Aroma System (I.P.B.A.S.®) Grinder High-performance pump, 15 bar Thermoblock heating system Fluid systems	Electrically adjustable ceramic disc grinder 2 2
Pulse Extraction Process (P.E.P.®) Variable VC brewing unit, from 5 g to 16 g Intelligent Pre-Brew Aroma System (I.P.B.A.S.®) Grinder High-performance pump, 15 bar Thermoblock heating system Fluid systems JURA fine foam technology	Electrically adjustable ceramic disc grinder 2 2 2
Pulse Extraction Process (P.E.P.®) Variable VC brewing unit, from 5 g to 16 g Intelligent Pre-Brew Aroma System (I.P.B.A.S.®) Grinder High-performance pump, 15 bar Thermoblock heating system Fluid systems JURA fine foam technology Milk system	Electrically adjustable ceramic disc grinder 2 2 2 HP3
Pulse Extraction Process (P.E.P.®) Variable VC brewing unit, from 5 g to 16 g Intelligent Pre-Brew Aroma System (I.P.B.A.S.®) Grinder High-performance pump, 15 bar Thermoblock heating system Fluid systems JURA fine foam technology Milk system Maintenance status display	Electrically adjustable ceramic disc grinder 2 2 2 HP3
Pulse Extraction Process (P.E.P.®) Variable VC brewing unit, from 5 g to 16 g Intelligent Pre-Brew Aroma System (I.P.B.A.S.®) Grinder High-performance pump, 15 bar Thermoblock heating system Fluid systems JURA fine foam technology Milk system Maintenance status display Integrated rinsing, cleaning and descaling programme Integrated milk system rinsing	Electrically adjustable ceramic disc grinder 2 2 2 HP3
Pulse Extraction Process (P.E.P.®) Variable VC brewing unit, from 5 g to 16 g Intelligent Pre-Brew Aroma System (I.P.B.A.S.®) Grinder High-performance pump, 15 bar Thermoblock heating system Fluid systems JURA fine foam technology Milk system Maintenance status display Integrated rinsing, cleaning and descaling programme Integrated milk system rinsing and cleaning programme	Electrically adjustable ceramic disc grinder 2 2 2 HP3
Pulse Extraction Process (P.E.P.®) Variable VC brewing unit, from 5 g to 16 g Intelligent Pre-Brew Aroma System (I.P.B.A.S.®) Grinder High-performance pump, 15 bar Thermoblock heating system Fluid systems JURA fine foam technology Milk system Maintenance status display Integrated rinsing, cleaning and descaling programme Integrated milk system rinsing	Electrically adjustable ceramic disc grinder 2 2 2 HP3
Pulse Extraction Process (P.E.P.®) Variable VC brewing unit, from 5 g to 16 g Intelligent Pre-Brew Aroma System (I.P.B.A.S.®) Grinder High-performance pump, 15 bar Thermoblock heating system Fluid systems JURA fine foam technology Milk system Maintenance status display Integrated rinsing, cleaning and descaling programme Integrated milk system rinsing and cleaning programme	Electrically adjustable ceramic disc grinder 2 2 2 HP3
Pulse Extraction Process (P.E.P.®) Variable VC brewing unit, from 5 g to 16 g Intelligent Pre-Brew Aroma System (I.P.B.A.S.®) Grinder High-performance pump, 15 bar Thermoblock heating system Fluid systems JURA fine foam technology Milk system Maintenance status display Integrated rinsing, cleaning and descaling programme Integrated milk system rinsing and cleaning programme JURA hygiene: TÜV-certified	Electrically adjustable ceramic disc grinder 2 2 2 HP3 CLARIS Pro Smart maxi/CLARIS Pro

Programmable and individually adjustable amount of water	
Programmable and individually	
adjustable coffee strength	10 steps
Programmable milk/milk foam temperature	10 steps
Store, copy and personalise products	_
Programmable brewing temperature	3 steps
Programmable amount of milk/milk foam	_
Programmable temperature of hot water	3 steps
Resettable day counter	•
Programmable switch-on/switch-off time	•
Shows the number of preparations	_
for each individual product	•
Design and materials	
Alu Frame Design® 3 mm	
Display	TFT touchscreen colour display
Amber/white cup illumination	
Powder chute for ground coffee	_
Sound design	
In figures	
Height-adjustable dual spout	70 – 159 mm
Height-adjustable hot-water spout	69 – 165 mm
Water tank capacity	51
Bean container holding capacity	1kg
Coffee grounds container (servings)	max. 40
Cable length	approx. 1.1 m
Voltage / Power	220 – 240 V~/2300W
Current	10A
Stand-by power	<0.5 W
	19 kg
Weight	13 119
Weight Dimensions (W×H×D)	37×56.5×49.7 cm



EAN code

Hygiene standards



7610917152292

Zero-Energy Switch or power switch