



FEATURES

- >> Ultra modern design with high heat dissipation
- >> 150lm/w High Intensity light output
- >> Low power consumption
- Long life endurance
- >> CE, RoHS, SAA

APPLICATIONS

- Office
- Warehouse
- Library

- Supermarket
- Train station
- Workshop

- Factory
- Airport
- Sports Arena

- Cinema
- Resturants
- Building exterior

Intertek	DI.c	C€	RoHS	SAA
----------	------	----	------	-----

GENERAL SPECIFICATIONS				
Models	ETG-SHBL-120 / 150 /200			
Input Voltage	100-277 VAC			
Lm/W	150lm/W			
Lumen Range	18,000 ~ 30,000			
IP Rating	IP65			
Light Source	Lumileds			
Material	Aluminum, PC & Glass			
Beam Angle	80° / 90°/ 110°			
CCT	4000K/5000K/5700K			
CRI	>70			
Mounting	Eye bolt hook			
Lifespan	>50,000			
Warranty	5 Years			





SPECIFICATION











			HIREFI DER	
MODEL	ETG-SHBL120	ETG-SHBL150	ETG-SHBL200	
Power(W)	120W	150W	200W	
Light Source	Lumileds	Lumileds	Lumileds	
CCT(K)	4000K, 5000, 5700K	4000K, 5000, 5700K	4000K, 5000, 5700K	
IP Rating	IP65	IP65	IP65	
AC Input	100-277 VAC	100-277 VAC	100-277 VAC	
Operating Temperature	-30°C to +50°C 10% to 90% RH	-30°C to +50°C 10% to 90% RH	-30°C to +50°C 10% to 90% RH	
Lm/W	150lm/W	150lm/W	150lm/W	
Lumen (lm)	18,000lm	22,500lm	30,000lm	
Power Factor	>0.97	>0.97	>0.97	
CRI	70	70	70	
Lifespan	>50,000 Hrs	>50,000 Hrs	>50,000 Hrs	
Warranty	5 Years	5 Years	5 Years	
Net Weight	4.0 Kg	4.8Kg	5.6Kg	

DIMENSIONS


SATURN SERIES



ETG-SHBL-120





ETG-SHBL-150




ETG-SHBL-200

PHOTOMETRIC DIAGRAM SATURN SERIES







80

90

120

ACCESSORIES SATURN SERIES







DISCLAIMER

Important Statement of warranty.

Earthtrack reserves the right to change or discontinue a product and / or specification without notice. All warranty periods only cover faulty workmanship and / or material components. Any claims on misused or disassembled products will not be recognized by Earthtrack. All information enclosed in this catalogue, to our knowledge, was correct at time of print.

