

Specifications

LED Module: Tridonic | Osram | Vossloh Schwabe | Samsung
Lumen Maintenance & Life Expectancy: L80 B10 >50,000h
Lumen Output Range: 1100 - 4800lm/m
Profile Dimensions: W60mm x H38mm | **Length:** Min 310mm Max unlimited multiples of 140mm, 280mm and 560mm
Protection Rate: IP20 | IP54 on request
CRI: Ra80 | Ra90 on request
Colour Temperature: 3000K | 4000K | 27-57K Tunable White
Colour Stability: 3 Step MacAdam
Distribution: Direct
Diffuser: Ice
Dimming: Non-dim | DALI | 0-10V | Switch-dim
Warranty: 5 Years | Extended on request

Features: Mitered Corners | No visible fixings | Removable gear plates | Socket End Caps to prevent light leakage | Independent test reports

How to Specify

Follow the steps below to specify your requirements:

1 Select Profile & Colour	2 Select length	3 Select distribution	4 Select Kelvin & CRI	5 Select control	6 Select installation	7 Select extras
40SQR—## (Colour Suffix) 40SQR—CC (Custom Colour)	Specify in mm	Direct (DIR)	3000K 80Ra (3K) 4000K 80Ra (4K)	Non Dim (ND) DALI (DALI) 1-10V (10V) Switch (SW)	Recessed (REC)	Emergency (EM) DALI Sensor (DS) LED Downlights (DL) LED Spotlights (SL)

Specification Examples:

40SQR-WT-1200-DIR[2]-3K-DALI-CS
 40SQR-MB-2000-DIR[3]-4K-ND-WSP-EM

Lumen Maintenance & Life Expectancy


- All LED modules are selected from within 3 MacAdams.
- Independent LM79, LM80 and TM21 test reports are available on request.
- Independent photometric files are available on request.
- L80 B10 >50,000h

Lumen Output Suffix

Suffix	Lm/m	L80 B10
1	1100	50,000h
2	1600	50,000h
3	2600	50,000h
4	3700	50,000h
5	4800	50,000h

More outputs available on request

Colour Options



Custom colours and anodized finishes on request

Mounting Options



Dimensions & Construction

