

# Rolo & Dado

Rolo designed by Simon Fisher



## Body

Track mounted round spotlight with light-head and driver box in cast aluminium.

Available with 3 circuit universal track adapter, Dali track adapter or, for the low voltage version, mini track adapter. For retrofit version, easy relamping by the removable lamp front ring via simple snap-in catch action.

Versatile aiming angle tiltable vertically 0°-90° in two directions and rotatable horizontally 350°.

## LED sources

Citizen CLU series. SORAA SLE Optical Light Engine. CRI: 90, 95 | CCT: 3000K, 4000K. Other CRI and CCT options available on request.

## Optic

Lenses. Narrow, medium and wide beam angle available.

## Related Products



## Accessories

Honeycomb louvre, linear spread, Snap System™ accessories available for SORAA SLC series with narrow beam angle.

## Finish

Powder coat in white or grey colour.

## Driver

Driver box inclusive of no-dimable driver. Dimming Options: 0-10V Dim, DALI, Phase, CASAMBI.

## Applications

A versatile and very directional cylindrical spotlight. The very compact sizes make it ideal for applications where the distance between ceiling and spot is an issue. Application areas: retail, museums, residential, hospitality, window displays.

## Rolo



### Rolo

Eurotype Track



### Rolo

Low Voltage Track



Eurotype Track Low Voltage Track



Code ordering example: **6 2 8 8 B B 2 2 - 9 0 3 0 1 4 D 0 1 1**

	Product Code	Light Source Code*	>CRI	CCT**	LED Power	Nominal Lumen	Beam Angle (BA°)	Driver Options	Finish
Rolo Eurotype Track	<b>6288</b>	<b>BB22</b>	<b>90</b>	<b>30</b> 3000K	6W	706 lm	<b>14 / 24 / 34</b>	<b>D0</b> No Dim	<b>11</b> <input type="checkbox"/> White
				<b>40</b> 4000K		757 lm		<b>DA</b> Dali Dim	<b>75</b> <input type="checkbox"/> Grey
Rolo Low Voltage Track	<b>6093</b>	<b>GU53</b>	<b>00</b>	<b>00</b>	/	/	<b>00</b>	<b>DP</b> Phase Dim	
								<b>DC</b> CASAMBI	
								<b>D1</b> 0-10V Dim	
								<b>DP</b> Phase Dim <sup>†</sup>	

### Notes:

\* For complete code ordering information, please see page 377.

\*\* For other CCT options, please contact us.

† Remote electronic dimable transformer supplied with the track, for more information see page 168. For related accessories, please see page 165.

# Dado



## Dado

Eurotype Track



## Dado

Low Voltage Track



Eurotype Track Low Voltage Track



Code ordering example: 6 2 8 7 B B 2 2 - 9 0 3 0 1 4 D 0 1 1

	Product Code	Light Source Code*	>CRI	CCT**	LED Power	Nominal Lumen	Beam Angle (BA°)	Driver Options	Finish
Dado Eurotype Track	<b>6287</b>	<b>BB22</b>	<b>90</b>	<b>30</b> 3000K	6W	706 lm	<b>14 / 24 / 34</b>	<b>D0</b> No Dim	<b>11</b> <input type="checkbox"/> White
				<b>40</b> 4000K		757 lm		<b>DA</b> Dali Dim	
							<b>DP</b> Phase Dim		
							<b>DC</b> CASAMBI		
							<b>D1</b> 0-10V Dim		
Dado Low Voltage Track	<b>6094</b>	<b>GU53</b>	<b>00</b>	<b>00</b>	/	/	<b>00</b>	<b>DP</b> Phase Dim*	

**Notes:**

- \* For complete code ordering information, please see page 377.
  - \*\* For other CCT options, please contact us.
  - \* Remote electronic dimable transformer supplied with the track, for more information see page 168.
- For related accessories, please see page 165.

# Rolo & Dado Family configuration options

Code ordering example: 6 2 8 8 B B 2 2 - 9 0 3 0 1 4 D 0 1 1


## Rolo

Product Code	Light Source Code	>CRI	CCT	LED Power	Nominal Lumen	Beam Angle (BA°)	Driver Options	Finish
<b>6288</b> Eurotype Track	<b>BB22</b> Bridgelux COB	<b>90</b>	<b>30</b> 3000K	6W	706 lm	<b>14 / 24 / 34</b>	<b>D0</b> No Dim	<b>11</b> <input type="checkbox"/> White
			<b>40</b> 4000K		757 lm		<b>DA</b> Dali Dim	
	<b>BS12</b> Soraa SLC-16	<b>95</b>		8.1W	460 lm	<b>10</b>	<b>DP</b> Phase Dim	
					480 lm		<b>DC</b> CASAMBI	
				12.2W	720 lm	<b>15 / 25 / 36</b>	<b>D1</b> 0-10V Dim	
					755 lm			
	<b>GU53</b> Retrofit MR16-GU5.3	<b>00</b>	<b>00</b>	/	/	<b>00</b>	<b>DP</b> Phase Dim	
	<b>GU10</b> GZ10-GU10							
<b>6093</b> Low Voltage Track	<b>GU53</b> MR16-GU5.3							

## Dado

Product Code	Light Source Code	>CRI	CCT	LED Power	Nominal Lumen	Beam Angle (BA°)	Driver Options	Finish
<b>6287</b> Eurotype Track	<b>BB22</b> Bridgelux COB	<b>90</b>	<b>30</b> 3000K	6W	706 lm	<b>14 / 24 / 34</b>	<b>D0</b> No Dim	<b>11</b> <input type="checkbox"/> White
			<b>40</b> 4000K		757 lm		<b>DA</b> Dali Dim	
	<b>BS12</b> Soraa SLC-16	<b>95</b>		8.1W	460 lm	<b>10</b>	<b>DP</b> Phase Dim	
					480 lm		<b>DC</b> CASAMBI	
				12.2W	720 lm	<b>15 / 25 / 36</b>	<b>D1</b> 0-10V Dim	
					755 lm			
	<b>GU53</b> Retrofit MR16-GU5.3	<b>00</b>	<b>00</b>	/	/	<b>00</b>	<b>DP</b> Phase Dim	
	<b>GU10</b> GZ10-GU10							
<b>6094</b> Low Voltage Track	<b>GU53</b> MR16-GU5.3							

# Optical Accessories



Product / Optical Accessories	Linear Spread Colour 41	Honeycomb Louvre Colour 10
Rolo & Dado Track GU5.3	<b>2362</b>	<b>2361</b>

For Soraa specific accessories, please contact us and we will provide the detailed information.

**Notes:**

For other CCT options, please contact us.