

NEBULA



Choice of lighting levels up to 2560 lumens; over 750 lux @ 1 metre



Integrated switch & 5 minute PIR sensor/switch options



Waterproof to IP66



Robust construction with unique impact deflection design




E-type approved



TECHNICAL SPECS OVERLEAF 
MAY 2017



DESIGNED FOR MULTI-SECTOR APPLICATIONS




NEBULA

Long life, high intensity Cree LEDs - The Nebula incorporates the Orizon LED strip light, which uses the latest in LED technology, offering optimum performance and extended life. The properties of these LEDs give greater luminosity, allowing us to offer a brighter unit whilst using fewer LEDs to maintain the low power draw. The unit is available with 12, 24, 48 and 96 LEDs, offering a choice of light output and lengths to suit every application and every budget.

Integrated switch option - The Nebula can be switched remotely or is available with an integrated on/off rocker switch which fits neatly into the end cap. A 5 minute PIR* switch option is also available to enable automatic switching; if continuous movement is detected then the lights will remain on.

Waterproof to IP66 - The PCB driver, components and LEDs are completely encased within a polycarbonate extrusion, which protects against moisture ingress.

Tough aluminium housing - Set in a low profile, tough aluminium housing, the Nebula is quick and easy to install, making it suitable for both new vehicle specifications and retrofitting into existing vehicles.



X LENGTHS: SI5CW250 = 376MM : SI5CW250PIR = 420MM : SI5CW500 = 624MM : SI5CW500PIR = 668MM SI5CW1000 = 1124MM

SPECIFICATION

ALL DIMENSIONS HAVE A TOLERANCE OF +/-1mm

	12VDC	SI5CW250 (12 LED - 12V)	SI5CW500 (24 LED - 12V)	SI5CW1000 (48 LED - 12V)
Voltage Range	VDC	10-14	10-14	10-14
Average Current	A	0.24	0.44	1.0
Light Output	lm	320	640	1280
Watts	W	3W	6W	12W
Weight	kg	0.08	0.38	0.7
Temp. Range	°C	-30 to +40	-30 to +40	-30 to +40
IP Rating (switched*)	IP	IP60	IP60	IP60
IP Rating (non switched)	IP	IP66	IP66	IP66
	24VDC	SI5CW500 (12 LED - 24V)	SI5CW500 (24 LED - 24V)	SI5CW1000 (48 LED - 24V)
Voltage Range	VDC	20-28	20-28	20-28
Average Current	A	0.12	0.22	0.5
Light Output	lm	320	640	1280
Watts	W	3W	6W	12W
Weight	kg	0.08	0.38	0.7
Temp. Range	°C	-30 to +40	-30 to +40	-30 to +40
IP Rating (switched*)	IP	IP60	IP60	IP60
IP Rating (non switched)	IP	IP66	IP66	IP66

E & OE | Calculations based on average LED values @ 13.2V (for 12V models) and @ 26V (for 24V)

** LED strip = IP66

* PIR versions = 3 year warranty

