NEW FOR AHR 2014



## **BiMetal Line Voltage Thermostat** Product Line

тето

()

TP122, TP123, TP124

Tempro<sup>™</sup> thermostats are designed to accurately regulate precise temperature in commerical, industrial, and agricultural settings.

## **INTRODUCING** *BiMetal*

Tempro Bimetal thermostats are line voltage, snap action devices that accurately control your temperature requirements. Available to meet both ventilation or heating requirements, they are designed to operate in extreme conditions and are NEMA 1 rated. Tempro thermostats are a reliable and economical choice for many agricultural, industrial and commercial where dependability is a requirement

Тето

TP121, TP125



Flip For Complete Fact Sheet



	Line Vo	Line Voltage Thermostat BiMetal Product Line Fact Sheet				
τεμοιο	TP521	TP522	TP523	TP524	TP525	
Housing Construction	AG BiMetal Steel	AG BiMetal Steel	AG BiMetal Steel	AG BiMetal Steel	AG BiMetal Steel	
Function	Heat Only	Heat & Cooling	Heat Only	Cooling Only	Cooling Only	
Feature	Line Voltage Control	Ventilation Control	Line Voltage Control	Ventilation Control	Ventilation Control	
Switch Type	SPST	SPDT	SPST	SPST	SPST	
Temperature Range	-10 to 100°F	-10 to 100°F	-10 to 100°F	-10 to 100°F	-10 to 100°F	
Diff. (°F)	3.5°	3.5°	3.5°	3.5°	3.5°	
H x W x D	5 <sup>1/2</sup> x 2 x 2 <sup>5/8</sup>	5 <sup>1/2</sup> x 2 x 2 <sup>5/8</sup>	5 <sup>1/2</sup> x 2 x 2 <sup>5/8</sup>	5 <sup>1/2</sup> x 2 x 2 <sup>5/8</sup>	5 <sup>1/2</sup> x 2 x 2 <sup>5</sup>	
Pilot duty rated @ 125VA - 24/600VAC	✓	1	✓	1	✓	
L 873 CUL and UL 60730 Certified	✓	1	1	4	✓	
6' HSJ Cord w/ Piggyback Plug	1				√	
Amp Rating 120v						
Inductive	12	16	16	16	1.	
Locked Rotor	72	96	96	96	7:	
Resistive SPST/SPDT	12	22/16	22	22	1	
Amp Rating 208v						
Inductive	*	9.2	9.2	9.2	,	
Locked Rotor	*	55.2	55.2	55.2	3	
Resistive SPST/SPDT	*	22/9.2	22	22	k	
Amp Rating 240v						
Inductive	*	8	8	8	,	
Locked Rotor	*	48	48	48	,	
Resistive SPST/SPDT	*	22/8	22	22		
Amp Rating 277v						
Inductive	*	*	*	*	,	
Locked Rotor	*	*	*	*	ł	
Resistive SPST/SPDT	*	*	22	22	te construction of the second s	

All models include Celsius temperature scales with adhesive back for easy application. Stainless models have internal components of stainless or copper





www.**Temproducts**.com

Manufactured by KAMAL International LLC 537 E. 10th Ave., Suite 301 Bowling Green, KY 42101 Phone & Fax: 847-594-0250 - Email: Sales@kamalllc.com