

IR ENERGY INC. 563 BARTON STREET STONEY CREEK, ON L8E 5S1

22"

PHONE: (905) 664-9082 www.irenergy.ca

		\$\frac{*}{6} \frac{*}{0} \frac
SELECT DESIRED GAS:		
☐ NATURAL GAS ☐ PROPANE	OPTIONAL GAS CONNECTION COVER	33." BELOW*
SELECT DESIRED FINISH:	12.30	
☐ 304 STAINLESS STEEL ☐ BLACK POWDER COAT	12.00" —	
CUSTOM POWDER COAT SPECIFY:	PERSPECTIVE TOP VIEW	101.7" –
TECHNICAL SPECIFICATIONS: - HIGH FIRE - 53,000BTU/HR (NG) 47,000BTU/HR (LPG) - LOW FIRE - 46,000BTU/HR (NG) 40,000BTU/HR (LPG) - MANIFOLD PRESSURE: NG - 5.5" W.C. (HI), 4.0" W.C. (LO) LPG -	FRONT AND SIDE ELEVATION HEAT COVERAGE	
9.8" W.C. (HI), 7.0" W.C. (LO) GAS SUPPLY PRESSURE: NG - 6.5" W.C. (MIN), 14.0" W.C. (MAX) LPG: 11.0" W.C. (MIN), 14.0" W.C. (MAX) ELECTRICAL SUPPLY: 24 VOLTS, 0.8	10, 0	7.875" - FRONT ELEVATION - MODEL GA301-T
AMPS - DIRECT SPARK IGNITION WITH 3-TRY LOCK OUT & AUTOMATIC RE-LIGHT WARRANTY: - 3 YEARS ON 316 STAINLESS STEEL	12'	6.300" 6.3
EMITTER	TYPICAL COVERAGE TYPICAL COVERAGE	1

NOTES:

- 1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 2. DO NOT SCALE DRAWING.

- 1 YEAR ON ALL OTHER PARTS

3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.

ONE HEATER

BOTTOM MOUNTING PLATE

- 4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
- CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5029-014.

TWO HEATERS



5029-014 REVISION DATE 09/01/2018