


IR ENERGY INC. 563 BARTON STREET STONEY CREEK, ON L8E 5S1

PHONE: (905) 664-9082 www.irenergy.ca



SPECIFICATIONS	PROPANE	NATURAL GAS
MANIFOLD	3.5" W.C. (HI),	10.5" W.C. (HI), 6.2
PRESSURE	2.4 W.C (LO)	W.C (LO)
INLET	11.5 W.C (MIN),	5.0" W.C (MIN), 14.0
PRESSURE	14.0" W.C. (MAX)	W.C (MAX)
INLET CONNECTION	1/2" MALE NPT	1/2" MALE NPT
ELECTRIC SUPPLY	120 VAC, 60 HZ, 1 AMP 36" CORD WITH	
	GROUNDED 3 PRONG PLUG	
CONTROL	TWO-STAGE SWITCH - PART #EE020	

CLEARANCES TO COMBUSTIBLES		
REFLECTOR CONFIGURATION	DIMENSION	MODEL NO ET10 (75,000 - 100,000 BTU/HR - 20FT)
STANDARD	Α	2"
	В	30"
	С	67"
	D	30"
45° TILT	A	4"
	В	4"
	С	67"
	D	58"

WARRANTY:

- 3 YEAR BURNER AND CONTROLS
- 10 YEAR ON ALUMINIZED HEAT EXCHANGER WITH POST PURGE

NOTES

- 1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 2. DO NOT SCALE DRAWING.
- 3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
- 4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
- CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5029-013.



EVENTUBE


EVENTUBE DUAL COMFORT SERIES: MODEL ET10N/P - 75,000BTU/HR (LO), 100,000BTU/HR (HI), 20FT, NATURAL GAS OR PROPANE

5029-013 REVISION DATE 12/06/2017



IR ENERGY INC. 563 BARTON STREET STONEY CREEK, ON L8E 5S1

PHONE: (905) 664-9082 www.irenergy.ca



SPECIFICATIONS	PROPANE	NATURAL GAS
MANIFOLD	3.5" W.C. (HI),	10.5" W.C. (HI), 6.2
PRESSURE	2.4 W.C (LO)	W.C (LO)
INLET	11.5 W.C (MIN),	5.0" W.C (MIN), 14.0
PRESSURE	14.0" W.C. (MAX)	W.C (MAX)
INLET CONNECTION	1/2" MALE NPT	1/2" MALE NPT
ELECTRIC SUPPLY	120 VAC, 60 HZ, 1 AMP 36" CORD WITH	
	GROUNDED 3 PRONG PLUG	
CONTROL	TWO-STAGE SWITCH - PART #EE020	

CLEARANCES TO COMBUSTIBLES		
REFLECTOR CONFIGURATION	DIMENSION	MODEL NO ET08 (60,000 - 80,000 BTU/HR - 20FT)
STANDARD	Α	2"
	В	26"
	С	67"
	D	30"
45° TILT	Α	4"
	В	4"
	С	67"
	D	58"

WARRANTY:

- 3 YEAR BURNER AND CONTROLS
- 10 YEAR ON ALUMINIZED HEAT EXCHANGER WITH POST PURGE

NOTES:

- 1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 2. DO NOT SCALE DRAWING.
- 3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
- 4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
- 5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5029-012.




5029-012 REVISION DATE 12/06/2017



IR ENERGY INC. 563 BARTON STREET STONEY CREEK, ON L8E 5S1 PHONE: (905) 664-9082

www.irenergy.ca



SPECIFICATIONS	NATURAL GAS	
MANIFOLD PRESSURE	3.5" W.C. (HI), 2.4" W.C (LO)	
INLET PRESSURE	5.0" W.C (MIN), 14.0 W.C (MAX)	
ELECTRIC SUPPLY	120 VAC, 60 HZ, 1 AMP 36" CORD WITH	
	GROUNDED 3 PRONG PLUG	
CONTROL	TWO-STAGE SWITCH - PART #EE020	

CLEARANCES TO COMBUSTIBLES		
REFLECTOR CONFIGURATION	DIMENSION	MODEL NO ET06 (45,000 - 60,000 BTU/HR - 15FT)
STANDARD	Α	2"
	В	25"
	С	58"
	D	25"
45° TILT	Α	4"
	В	4"
	С	50"
	D	46"

WARRANTY:

- 3 YEAR BURNER AND CONTROLS
- 10 YEAR ON HEAT TREATED ALUMINIZED TUBE

NOTES:

- 1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 2. DO NOT SCALE DRAWING.
- 3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
- 4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
- 5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5029-011.



EVENTUBE


EVENTUBE DUAL COMFORT SERIES: MODEL ET06N - 45,000BTU/HR (LO), 60,000BTU/HR (HI), 15FT, NATURAL GAS ONLY

5029-011 REVISION DATE 31/05/2017



IR ENERGY INC. 563 BARTON STREET STONEY CREEK, ON L8E 5S1

PHONE: (905) 664-9082 www.irenergy.ca



SPECIFICATIONS	PROPANE	NATURAL GAS
MANIFOLD	10.5" W.C. (HI),	3.5" W.C. (HI), 2.4"
PRESSURE	6.2" W.C (LO)	W.C (LO)
INLET	11.5 W.C (MIN),	5.0" W.C (MIN), 14.0
PRESSURE	14.0" W.C. (MAX)	W.C (MAX)
INLET CONNECTION	1/2" MALE NPT	1/2" MALE NPT
ELECTRIC SUPPLY	120 VAC, 60 HZ, 1 AMP 36" CORD WITH	
	GROUNDED 3 PRONG PLUG	
CONTROL	TWO-STAGE SWITCH - PART #EE020	

CLEARANCES TO COMBUSTIBLES		
REFLECTOR	DIMENSION	MODEL NO ET04
CONFIGURATION		(30,000 - 40,000
		BTU/HR - 10FT)
STANDARD	Α	2"
	В	18"
	С	45"
	D	18"
45° TILT	Α	4"
	В	4"
	С	40"
	D	38"

WARRANTY:

- 3 YEAR BURNER AND CONTROLS
- 10 YEAR ON ALUMINIZED HEAT EXCHANGER WITH POST PURGE

NOTES:

- 1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 2. DO NOT SCALE DRAWING.
- 3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
- 4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
- CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5029-010.



EVENTUBE

EVENTUBE DUAL COMFORT SERIES: MODEL ET04N/P - 30,000BTU/HR (LO), 40,000BTU/HR (HI), 10FT, NATURAL GAS OR PROPANE

5029-010 REVISION DATE 31/05/2017