



FLOOD LIGHTS



ILLUMINATOR SERIES

5
YEARS
WARRANTY

65
IP RATING

>80
CRI

LIFE SPAN
MORE THAN
50,000 Hrs



ETG-ILF100



ETG-ILF150



ETG-ILF200



ETG-ILF250



MODEL	ETG-ILF100	ETG-ILF150	ETG-ILF200	ETG-ILF250
Power	100W	150W	200W	250W
Lamp efficiency	130lm/W	130lm/W	130lm/W	130lm/W
Lumen	13,000 lm	19,500 lm	26,000 lm	32,500 lm
CCT(K)	2200K / 7000K	2200K / 7000K	2200K / 7000K	2200K / 7000K
LED Chips	Phillips 3030	Phillips 3030	Phillips 3030	Phillips 3030
Input Voltage	90-305V 50/60Hz	90-305V 50/60Hz	90-305V 50/60Hz	90-305V 50/60Hz
Operating Temperature	-25°C ~ +45°C	-25°C ~ +45°C	-25°C ~ +45°C	-25°C ~ +45°C
IP Rating	IP65	IP65	IP65	IP65
Rotatable	180 Degree	180 Degree	180 Degree	180 Degree
Driver	Meanwell HLG	Meanwell HLG	Meanwell HLG	Meanwell HLG
Beam Angle	60° 90° 60x135° 85x135°			
CRI	>80	>80	>80	>80
Lifespan	>50,000	>50,000	>50,000	>50,000
Dimension (mm)	298 x 320 x 104	398 x 320 x 104	503 x 320 x 104	609 x 320 x 104
Weight	4.5kg	6.5kg	9.0kg	11.5kg
Housing	ALU alloy + PC Cover	ALU alloy + PC Cover	ALU alloy + PC Cover	ALU alloy + PC Cover
Warranty	5 Years	5 Years	5 Years	5 Years