

METRO CURVE SERIES





- Adjustable knuckle bracket included
- Sleek and smooth body diminishes dust accumulation
- Water proof cover and anti-corrosion
- Energy conservation and environmental protection
- Tool-free replacement and Easy maintenance














MODEL	ETG-MCSL30	30 ETG-MCSL50 ETG-MCS		SL70	0 ETG-MCSL90		TG-MCSL120	ETG-MCSL150	
Power	30W	50W	70W		90W		120W	150W	
Lumen	3,900lm	6,500lm	9,100lm		11,700lm		15,600lm	18,750lm	
Driver	Sosen				Meanwell				
Luminous Efficacy	130lm/W / 125lm/W (150W)			IP Rating		IP66			
CCT(K)	4000K (Optional 3000K-5000K)			CRI		Ra70, Ra80			
LED Chips	Nichia Chip (Japan)			Protection Class		Class I			
Input Voltage	100-240 VAC 50/60Hz / 36-48 VDC			Beam Angle		Type II Medium Range			
Output Current	0.65A			Housing		ALU Alloy + PC Lens + Tempered Glass			
Operating Temp	-30°C ~ 45°C			Life Span		>50,000 (Ta=30°C@L70			
Power Factor	>0.90			Warranty		5 Years			

DIMENSIONS



OPTIONAL DAYLIGHT SENSOR



SPIGOT MOUNTING OPTION





Ø34mm

Ø42mm