



Australian Design Registration Number 344332

ENFORCER 60W

The Enforcer offers the very latest, high powered LED technology, ideal for use on heavy duty mining vehicles or construction equipment.

Superbly compact and exceptionally tough, the Enforcer has a substantial 145 degrees of adjustment, ensuring a solution to the most demanding applications.

The Enforcer features revolutionary high output optics that produce optimum light levels, along with the utilization of high quality Cree XP-G LEDs, controlled by Electronic Thermal Control.

Electronic Thermal Management (ETM)

ETM monitors the heat output of the LEDs and makes use of integrated Pulse Width Modulation circuitry in order to maintain safe operating temperatures which prolong the LED life span to its full 50,000 hours.


Pulse Width Modulation (PWM)

PWM dimming circuitry is used by the Enforcer to manage heat levels. PWM works by flashing the LED at a frequency faster than the human eye can detect, reducing the time that the LED is operating while still delivering 100% light output.

MOUNTING OPTION



DIMENSIONS



5 WATT
LEDs



9V-32V
MULTI-VOLT



IP69
WATERPROOF



50,000 HR
LIFESPAN



25G RMS
VIBRATION



AL 6061
HOUSING



IMPACT
RESISTANT



LOW
POWER DRAW





SPECIFICATIONS

Wattage	60 Watt
Light Source	12 × 5W Cree LEDs
Light Output	5,910 Lumen
Voltage	9V-32V DC
Current Draw	5A @ 12V
Operating Temp.	-40°C to +80°C
Vibration	25G rms
IP Rating	IP69
Connector Type	Deutsch DT 2 Pin
Housing	Die-Cast Alloy
Lens Construction	Polycarbonate
Bracket	5mm 316 Stainless Steel
Lifespan	50,000 Hours
Net Weight	2.5 kg (5.5 lbs.)
Mounting Suitable	Upright & Pendent
Beams Available	Wide Flood & Euro
Warranty	5 Years
Dimming Control	Yes (Optional)

PART NUMBERS

Euro Beam	EV512LEDEU/S
Wide Flood Beam	EV512LEDWF/S



15 10 5 2 1 0.5 lux