Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015) Issue date: 2023-03-31 Revision date: 2023-03-31 Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture

Product name : Heavy Duty Stainless Steel Wipes

Product code : TW40-SS, TW01-SS

1.2. Recommended use and restrictions on use

Recommended use : Cleaning wipes

1.3. Supplier

Manufacturer

SylBarrie Graphics 1593 Kale Drive Innisfil, ON Canada

T 705-792-6981 - F 705-792-1211

www.sylbarrie.com

1.4. Emergency telephone number

Emergency number : NEED

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 1B H350 May cause cancer.

2.2. GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms (GHS-CA) :





Signal word (GHS CA) : Danger

Hazard statements (GHS-CA) : H317 - May cause an allergic skin reaction.

H350 - May cause cancer.

Precautionary statements (GHS-CA) : P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 - IF exposed or concerned: Get medical advice/attention.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P362+P364 - Take off contaminated clothing and wash it before reuse. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2023-03-31 (Revision date) EN (English) 1/10

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Distillates, petroleum, hydrotreated middle	Petroleum distillates, hydrotreated middle / Distillates (petroleum), hydrotreated middle / Hydrotreated middle distillate (petroleum) / Distillates, petroleum, hydrotreated middle (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11-25 and boiling in the range of approximately 205-400°C.) / Petroleum distillate, hydrogenated, middle / C13-15 ALKANE / Distillates(petroleum), hydrotreated middle / Distillates (petroleum), hydrotreated middle; Gasoil - unspecified [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately; 205°C to 400°C (401°F to 752°F).] / c13-15 alkane	CAS-No.: 64742-46-7	80 < 100
White mineral oil, petroleum	White oil / White mineral oil (petroleum) / Oils, white mineral, petroleum / White mineral oil / Mineral oil, white / Mineral oils, petroleum / White mineral oil, petroleum (A highly refined petroleum mineral oil consisting of a complex combination of hydrocarbons obtained from the intensive treatment of a petroleum fraction with sulfuric acid and oleum, or by hydrogenation, or by a combination of hydrogenation and acid treatment. Additional washing and treating steps may be included in the processing operation. It consists of saturated hydrocarbons having carbon numbers predominantly in the range of C15-50.) / mineral oil / liquid paraffin / Paraffin oil / Mineral oil / Petroleum paraffinic oil / Distillates (petroleum), hydrotreated middle / Petroleum mineral oil / Petroleum oil / Mineral oils	CAS-No.: 8042-47-5	5 - 10

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%
D-Limonene	Limonene, d- / d-Limonene / 1-Methyl-4-prop-1-en-2-yl-cyclohexene / (R)-1-Methyl-4-(1-methylethenyl)cyclohexene / d-LIMONENE / Menthadiene, 1,8(9)-p- / Limonene, D- / Limonene / Limonene, (+)- / p-Mentha-1,8-diene, (R)-(+)- / (R)-p-Mentha-1,8-diene / Cyclohexene, 1-methyl-4-(1-methylethenyl)-, (R)- / Cyclohexene, 1-methyl-4-(1-methylethenyl)-, (4R)- / (4R)-1-Methyl-4-(1-methylethenyl)cyclohexene / (4R)-p-Mentha-1,8-diene / (R)-1-Methyl-4-(1-methylethenyl)cyclohex-1-ene / (R)-4-Isopropenyl-1-methylcyclohex-1-ene	CAS-No.: 5989-27-5	0.1 < 1

Comments : *Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Not a normal route of exposure. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before
	reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Not a normal route of exposure. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: Not a normal route of exposure. May cause irritation to the respiratory tract.
, ·	. , , , , , , , , , , , , , , , , , , ,
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause
	an allergic skin reaction.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear
	production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May result in obstruction and irritation if ingested. May cause
	gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	· May cause cancer

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use water jet.

5.3. Specific hazards arising from the hazardous product

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

2023-03-31 (Revision date) EN (English) 3/10

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting

: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2. Methods and materials for containment and cleaning up

For containment

: Pick up large pieces, then place in a suitable container. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up

: Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Obtain special instructions before use. Do not handle until all safey precautions have been read and understood. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.

Hygiene measures

: Take off contaminated clothing and wash it before reuse. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep out of the reach of children. Keep container tightly closed. Store locked up. Store in a dry, cool and well-ventilated place. Store away from foodstuffs.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

White mineral oil, petroleum (8042-47-5)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA 5 mg/m³ (mist)

8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.

Environmental exposure controls

: Avoid release to the environment.

2023-03-31 (Revision date) EN (English) 4/10

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration. Consult glove manufacturer's product information on material suitability and material thickness.

Eye protection:

Safety glasses or goggles are recommended when using product.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Wipes saturated with liquid.

Colour : Clear

Odour : No data available Odour threshold : No data available : No data available рΗ : No data available Relative evaporation rate (butylacetate=1) : No data available Relative evaporation rate (ether=1) Melting point : No data available Freezing point : No data available Boiling point : Not determined Flash point : > 100 °C Closed cup Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) : Not flammable : No data available Vapour pressure : No data available Relative vapour density at 20°C : No data available Relative density Solubility : No data available Partition coefficient n-octanol/water No data available

Viscosity, kinematic : Not applicable (no free liquid)

Explosive limits : No data available

White mineral oil, petroleum (8042-47-5)	
Boiling point	218 – 800 °C Atm. press.: 101,3 kPa
Flash point	> 112 °C Atm. press.: 101,3 kPa
Vapour pressure	≤ 0.01 kPa Temp.: 20 °C

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

D-Limonene (5989-27-5)	
Boiling point	176 °C
Flash point	51 °C Atm. press.: 1 atm
Auto-ignition temperature	237 °C
Vapour pressure	200 Pa Temp.: 298 K

Distillates, petroleum, hydrotreated middle (64742-46-7)	
Boiling point	172 – 379 °C Atm. press.: 101,3 kPa Remarks on result: 'other:'
Flash point	> 56 °C
Auto-ignition temperature	> 200 °C (at 1013 hPa)
Vapour pressure	0.4 kPa Temp.: 40 °C

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity : No dangerous reactions known under normal conditions of use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.

Conditions to avoid : Heat. Incompatible materials.

Incompatible materials : Strong oxidizers.

Hazardous decomposition products : May include, and are not limited to: oxides of carbon.

Hardening time: : No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Not classified.

White mineral oil, petroleum (8042-47-5)		
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LC50 inhalation rat	> 5 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)	
D-Limonene (5989-27-5)		
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)	
LD50 dermal rabbit	> 5 g/kg	
Distillates, petroleum, hydrotreated middle (64742-46-7)		
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Skin corrosion/irritation : Not classified.
Serious eye damage/irritation : Not classified.

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified.

Carcinogenicity : May cause cancer.

D-Limonene (5989-27-5)	
IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity

Reproductive toxicity : Not classified.

Distillates, petroleum, hydrotreated middle (64742-46-7)	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male

STOT-single exposure : Not classified. STOT-repeated exposure : Not classified.

White mineral oil, petroleum (8042-47-5)	
	≥ 1200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Aspiration hazard : Not classified.

Heavy Duty Stainless Steel Wipes	
Viscosity, kinematic	Not applicable (no free liquid)
White mineral oil, petroleum (8042-47-5)	
Animal studies and expert judgment for classification	False
D-Limonene (5989-27-5)	
Animal studies and expert judgment for classification	False

Distillates, petroleum, hydrotreated middle (64742-46-7)	
Viscosity, kinematic	2 – 8.1 mm²/s Temp.: '40°C' Parameter: 'mm²/smm2/s'
Animal studies and expert judgment for classification	Falso

Animal studies and expert judgment for classification | False |
Symptoms/effects after inhalation : Not a normal route of exposure. May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction.

Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear

production, with possible redness and swelling.

Symptoms/effects after ingestion : May be harmful if swallowed. May result in obstruction and irritation if ingested. May cause

gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic symptoms : May cause cancer.

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Not classified.

(acute)

Hazardous to the aquatic environment, long-term : Not classified.

(chronic)

2023-03-31 (Revision date) EN (English) 7/10

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

White mineral oil, petroleum (8042-47-5)		
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)	
D-Limonene (5989-27-5)		
LC50 - Fish [1]	720 μg/l Test organisms (species): Pimephales promelas	
LC50 - Fish [2]	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
EC50 - Crustacea [1]	0.36 mg/l Test organisms (species): Daphnia magna	
EC50 - Crustacea [2]	0.51 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	\approx 8 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)	
EC50 72h - Algae [2]	0.214 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
NOEC (chronic)	0.115 mg/l Test organisms (species): other:For freshwater invertebrates, species frequently include Daphnia magna or Daphnia pulex. Duration: '16 d'	
Distillates, petroleum, hydrotreated middle (64742-46-7)		
LC50 - Fish [1]	35 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
LC50 - Fish [2]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	

12.2. Persistence and degradability

Heavy Duty Stainless Steel Wipes	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Heavy Duty Stainless Steel Wipes		
Bioaccumulative potential	Not established.	
White mineral oil, petroleum (8042-47-5)		
Partition coefficient n-octanol/water	> 6	
D-Limonene (5989-27-5)		
Partition coefficient n-octanol/water	4.38 (at 37 °C (at pH 7.2)	

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified.

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2023-03-31 (Revision date) EN (English) 8/10

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 14: Transport information

In accordance with TDG / IMDG / IATA

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

14.3. Transport hazard class(es)

TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (TDG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

TDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

2023-03-31 (Revision date) EN (English) 9/10

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

15.2. International regulations

No additional information available

SECTION 16: Other information

Issue date : 03-31-2023 Revision date : 03-31-2023

Other information : None.

Prepared by : Nexreg Compliance Inc.

SylBarrie Translations Ltd.

www.sylbarrie.com/ www.Nexreg.com



Safety Data Sheet (SDS), Canada - Nexreg 2022

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

2023-03-31 (Revision date) EN (English) 10/10