

# **Safety Data Sheet**

AQUENCE KL 442.3051 known as DORUS KL 442.3051 1100KG SHZ

SDS No.: 429285

V001.4

Page 1 of 6

Date of issue: 23.09.2021

# Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: AQUENCE KL 442.3051 known as DORUS KL 442.3051 1100KG SHZ

**Intended use:** Adhesive

Supplier:

Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137

Australia

Phone: +61 (3) 9724 6444

**Emergency information:** 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

# Section 2. Hazards identification

#### Classification of the substance or mixture

Not hazardous according to the criteria of Safe Work Australia.

## **GHS Classification:**

No classification required.

### **Dangerous Goods information:**

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

## Section 3. Composition / information on ingredients

General chemical description: Mixture

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
vinyl acetate	108-05-4	< 1 %
non hazardous ingredients~		60- <= 100 %

Page 2 of 6

SDS No.: 429285 V001.4

AQUENCE KL 442.3051 known as DORUS KL 442.3051

1100KG SHZ

Section 4. First aid measures

**Ingestion:** Rinse out mouth. Do not drink.

In case of adverse health effects seek medical advice.

Skin: Rinse with running water and soap.

If symptoms develop and persist, get medical attention.

Eyes: Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if

necessary.

**Inhalation:** Move to fresh air. If symptoms persist, seek medical advice.

First Aid facilities: Eye wash

Normal washroom facilities

Medical attention and special

treatment:

Treat symptomatically.

## Section 5. Fire fighting measures

Suitable extinguishing media: Use media appropriate for surrounding material.

Combustion behaviour: Non-flammable (aqueous solution).

Decomposition products in case of

Thermal decomposition can lead to release of irritating gases and vapors.

re: Oxides of carbon.

Special protective equipment for

fire-fighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

#### Section 6. Accidental release measures

**Personal precautions:** See advice in section 8

Danger of slipping on spilled product.

**Environmental precautions:** Do not empty into drains / surface water / ground water.

**Clean-up methods:** For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for

disposal.

# Section 7. Handling and storage

**Precautions for safe handling:** See advice in section 8

Wear suitable protective clothing, gloves and eye/face protection.

**Conditions for safe storage:** Store in a cool, well-ventilated place.

Keep container tightly sealed and store in a frost free place.

Storage temperature between 5 and 35°C.

## Section 8. Exposure controls / personal protection

Page 3 of 6

SDS No.: 429285 V001.4

AQUENCE KL 442.3051 known as DORUS KL 442.3051

1100KG SHZ

#### National exposure standards:

Ingredient [Regulated substance]	form of	TWA (ppm)	TWA	Peak Limit.	Peak Limit.	STEL (ppm)	STEL
	exposure		(mg/m3)	(ppm)	(mg/m3)		(mg/m3)
VINYL ACETATE		10	35				
108-05-4							
VINYL ACETATE						20	70
108-05-4							

**Engineering controls:** Ensure adequate ventilation.

**Eye protection:** Safety glasses.

**Skin protection:** Use of protective coveralls and long sleeves is recommended.

Suitable protective gloves.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed

then the gloves should be replaced.

Respiratory protection: If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

## Section 9. Physical and chemical properties

Appearance: White emulsion
Odor: mild

 Odor:
 mild

 pH:
 2.9 - 3.5

 Solubility in water:
 Miscible

 Viscosity (dynamic):
 3,500 - 5,000 mPa.s

Viscosity (dynamic): (; 23 °C (73.4 °F); speed of rotation: 20 min-1; Spindle No:

4; Method: ;; viscosity,

Brookfield)

# Section 10. Stability and reactivity

**Stability:** Stable under normal conditions of temperature and pressure.

Conditions to avoid: Excessive heat.

**Incompatible materials:** None known

Hazardous decomposition

products:

Carbon dioxide, carbon monoxide and irritating and/or toxic gases and particulate may be

generated by thermal decomposition or combustion.

# Section 11. Toxicological information

SDS No.: 429285 V001.4

# AQUENCE KL 442.3051 known as DORUS KL 442.3051

1100KG SHZ

**Health Effects:** 

**Ingestion:** Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea,

and diarrhea.

**Skin:** Prolonged or repeated contact may cause irritation.

Eyes: May cause mild irritation

**Inhalation:** Inhalation of mist or spray may cause irritation of the respiratory tract and nasal passages.

#### Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
vinyl acetate	LD50	3,500 mg/kg	oral		rat	not specified
108-05-4	Acute	11.27 mg/l	inhalation			Expert judgement
	toxicity	4490 ppm	inhalation	4 h	rat	not specified
	estimate	7,440 mg/kg	dermal		rabbit	not specified
	(ATE)					
	LC50					
	LD50					

#### Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
vinyl acetate	not irritating	4 h	rabbit	OECD Guideline 404 (Acute
108-05-4				Dermal Irritation / Corrosion)

#### Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
vinyl acetate	not irritating		rabbit	OECD Guideline 405 (Acute
108-05-4				Eye Irritation / Corrosion)

#### Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
vinyl acetate 108-05-4	not sensitising	Mouse local lymphnod e assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

## Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
vinyl acetate 108-05-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
vinyl acetate 108-05-4	ambiguous	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

## Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
vinyl acetate 108-05-4	NOAEL=5000 ppm	oral: drinking water	3 mdaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

# Section 12. Ecological information

Page 5 of 6

SDS No.: 429285 V001.4

# AQUENCE KL 442.3051 known as DORUS KL 442.3051

1100KG SHZ

General ecological information:

Do not empty into drains / surface water / ground water.

## Toxicity:

Hazardous components	Value	Value	Acute	Exposure	Species	Method
CAS-No.	type		Toxicity	time		
			Study			
vinyl acetate	LC50	26 mg/l	Fish	48 h	Leuciscus idus melanotus	OECD Guideline
108-05-4						203 (Fish, Acute
						Toxicity Test)
vinyl acetate	NOEC	0.551 mg/l	Fish	34 d	Pimephales promelas	OECD Guideline
108-05-4						210 (fish early lite
						stage toxicity test)
vinyl acetate	EC50	12.6 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
108-05-4						202 (Daphnia sp.
						Acute
						Immobilisation
						Test)
vinyl acetate	NOEC	5.96 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline
108-05-4					_	201 (Alga, Growth
						Inhibition Test)
vinyl acetate	EC50	12.7 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline
108-05-4						201 (Alga, Growth
						Inhibition Test)

## Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
vinyl acetate 108-05-4	readily biodegradable	aerobic	82 - 98 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI
				Test (I))

#### Bioaccumulative potential / Mobility in soil:

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			
vinyl acetate	0.73				25 °C	other guideline:
108-05-4						

# Section 13. Disposal considerations

Waste disposal of product: Dispose of according to Federal, State and local governmental regulations.

Disposal for uncleaned package: Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

# Section 14. Transport information

#### Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the

Australian Code for the Transport of Dangerous Goods by Road and

Rail (ADG Code).

## Marine transport IMDG:

Not dangerous goods

## Air transport IATA:

Not dangerous goods

SDS No.: 429285

AQUENCE KL 442.3051 known as DORUS KL 442.3051

V001.4 AQUENCE K 1100KG SHZ

# Section 15. Regulatory information

SUSMP Poisons Schedule None

All components are listed or are exempt from listing on the Australian Inventory of

Chemical Substances (AICIS).

#### Section 16. Other information

Abbreviations/acronyms: ADGC - Australian Dangerous Goods Code

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

IMDG: International Maritime Dangerous Goods code AIIC - Australian Inventory of Industrial Chemicals (AIIC) AICIS - Australian Industrial Chemicals Introduction Scheme

**Reason for issue:** Reviewed SDS. Reissued with new date. involved chapters: 1 - 16

**Date of previous issue:** 13.09.2016

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.