

ULTRAFOAM +



Premium Caustic Foam Detergent - Long Cling Technology

Application Areas

ULTRAFOAM + is a premium caustic foam detergent for general foam cleaning of the plant and equipment in the food and beverage industry. Highly effective at removing fats, protein and grease. Excellent foam characteristics which provide a longer contact time with higher causticity. Suitable for all water types.

Direction of Use

Use **ULTRAFOAM +** at 3-5% v/v through suitable foam generating equipment at ambient temperatures.

Technical Details

Composition	Contains sodium hydroxide, sequestrants, surfactants and solvent
Appearance	Clear Liquid
Colour	Colourless
pH (1% v/v)	12.5 - 13.5
Specific Gravity	1.15
Solubility	Soluble in water
Freezing Point	<-5°C

Material Compatibility

ULTRAFOAM + can be used on all materials commonly used in the food and beverage industry, with the exception of mild steel, carbon steel, galvanised materials, copper and its alloys.

Test Kit

Use SOS Alkalinity products Hi/Low Test Kit. The test requires the reagents KS135-PA1-Phenolphthalein Indicator, KS133-ALK4-Alkalinity LR Titrant.

Storage

Keep container upright and tightly closed in a well-ventilated place, away from heat and direct sunlight. Protect from freezing. Store in original packaging between 0°C and 35°C.
Shelf life: Minimum of two years.

Precautionary Statements

Wear appropriate personal protective equipment when using the **ULTRAFOAM +**. Collect Spillage. Avoid release into the environment. Please read the product label before use and refer to the Safety Data Sheet for further details on chemical handling and disposal guidance.

Pack Size

1000 Litres
200 Litres
20 Litres
5 Litres