

BRUSH TEXTURING MACHINE SELECT B



The brush texturing machines of the Select B range are top working machines with which solid wooden panels are structured. Thanks to the **oscillating** brush units, an exceptional beautiful and high-quality finish on floor parts is obtained.



BOERE MACHINEFABRIEK
BRUGWEG 121
POSTBUS 8
2740 AA WADDINXVEEN

T +31.182-614400
F +31.182-618349
E INFO@BOERE.NL
I WWW.BOERE.NL



With this Select oscillating texturing brush machines, Boere elaborates on the modular machine concept as can be seen in all other Boere wide belt sanding machines : from 2 to 4 texturing brushes in a working width of 600 to 1300 mm, depending on the work to be carried out.

Standard the texturing brushes are provided with Michelin steel wire, thickness 0,38 mm, and/or with Nylon Abrasive, grain 46. The combination of these brushes is to customer specification.

Of course is it possible to provide the texturing brushes with another thickness steel wire and other grain sizes.

Brush texturing machine Select B

Top working, equipped with 2 to 4 texturing brush units

Working width : 600 - 1300 mm

Working height : 100 mm

Feed speed : 4 - 15 m/min

Standard specification, among others :

- The texturing brushes are adjustable in depth by means of a hand wheel
- The brushes oscillate approx. 20 mm widthwise
- Reversing system to change over the direction of rotation of the texturing brushes
- Frequency controlled feed speed with electronic digital read-out
- Electromotive height adjustment of the feed table
- Convenient control panel



Possible options :

- Pressure plattens instead of pressure rollers in order to hold workpieces longer
- Rotating fibre brush unit at the outfeed side for cleaning the workpieces
- In-line system for a constant working height of the conveyor belt
- Electronic digital counter with pre-setting for feed table
- Vacuum table
- In- and outfeed roller tables