


# TECHNICAL SPECIFICATIONS

## OZONE GENERATOR GM1-4 3.0



GM	OZONE CONCENTRATION		MAX OZONE PRODUCTION		MAX OXYGEN CONSUMPTION			MAX POWER (kW)	LENGTH x WIDTH x HEIGHT	WEIGHT
	g/m <sup>3</sup>	%	g/hour	lbs/day	m <sup>3</sup> /h*	l/min*	SCFH*			
GM1	150	10%	60	3.2	0.41	6.8	14	0.60	603 x 437 x 517 mm 23.7 x 17.2 x 20.3"	36 kg 79.3 lb
	200	13%	50	2.6	0.25	4.2	8.9			
	250	17%	40	2.1	0.16	2.6	5.6			
	300	20%	27	1.4	0.098	1.6	3.5			
GM2	150	10%	120	6.3	0.81	14	29	1.2	603 x 437 x 517 mm 23.7 x 17.2 x 20.3"	45 kg 99.2 lb
	200	13%	100	5.3	0.50	8.4	18			
	250	17%	80	4.2	0.32	5.3	11			
	300	20%	54	2.9	0.20	3.3	6.9			
GM3	150	10%	180	9.5	1.2	20	43	1.8	603 x 437 x 517 mm 23.7 x 17.2 x 20.3"	52 kg 114.6 lb
	200	13%	150	7.9	0.75	13	27			
	250	17%	120	6.3	0.48	7.9	17			
	300	20%	81	4.3	0.29	4.9	10			
GM4	150	10%	240	13	1.6	27	57	2.4	603 x 437 x 517 mm 23.7 x 17.2 x 20.3"	60 kg 132.2 lb
	200	13%	200	11	1.0	17	35			
	250	17%	160	8.3	0.63	11	22			
	300	20%	110	5.7	0.39	6.5	14			

The above figures can vary ±10% and apply under the cooling conditions recommended by Primozone.

\*These values assume gas properties are standardized at 0°C / 68°F and atmospheric pressure.