


TECHNICAL SPECIFICATIONS

OZONE GENERATOR GM6-48 2.0



GM	OZONE CONCENTRATION		MAX OZONE PRODUCTION**		MAX OXYGEN CONSUMPTION			MAX POWER (kW)	LENGTH x WIDTH x HEIGHT	WEIGHT
	g/m ³ *	%	g/hour	lbs/day	m ³ /h*	l/min*	SCFH*			
GM6	150	10%	360	19	2.4	41	86	3.6	793 x 420 x 602 mm 31.2 x 16.5 x 23.7"	85 kg 187 lbs
	200	13%	300	16	1.5	25	53			
	250	17%	240	13	0.95	16	34			
	300	20%	160	8.6	0.59	9.8	21			
GM12	150	10%	720	38	4.9	81	170	7.2	728 x 424 x 1193 mm 28.7 x 16.7 x 47"	230 kg 507 lbs
	200	13%	600	32	3.0	50	110			
	250	17%	480	25	1.9	32	67			
	300	20%	320	17	1.2	20	42			
GM18	150	10%	1100	57	7.3	120	260	10.8	728 x 424 x 1569 mm 28.7 x 16.7 x 61.8"	280 kg 617 lbs
	200	13%	900	48	4.5	75	160			
	250	17%	720	38	2.9	48	100			
	300	20%	490	26	1.8	29	62			
GM24	150	10%	1400	76	9.7	160	340	14.4	992 x 855 x 1634 mm 39 x 34 x 64.3"	470 kg 1 036 lbs
	200	13%	1200	63	6.0	100	210			
	250	17%	960	51	3.8	63	130			
	300	20%	650	34	2.4	39	83			
GM36	150	10%	2200	110	15	240	520	21.6	992 x 855 x 1634 mm 39 x 34 x 64.3"	570 kg 1 256 lbs
	200	13%	1800	95	9.0	150	320			
	250	17%	1400	76	5.7	95	200			
	300	20%	970	51	3.5	59	120			
GM48	150	10%	2900	150	19	320	690	28.8	992 x 855 x 2010mm 39 x 34 x 79.1	710 kg 1 565 lbs
	200	13%	2400	130	12	200	430			
	250	17%	1900	100	7.6	130	270			
	300	20%	1300	69	4.7	78	170			

The above figures can vary +/-10%

*These values assume gas properties are standardized at 0°C / 68°F and atmospheric pressure.

**At 10°C (50°F) cooling water temperature.