

Primozone GM6-48

Datasheet



KEY FEATURES

- Highest concentration 20 % wt
- Safe, quiet, reliable
- Re-thinking redundancy
- Modular
- Compact design

	Ozone Concentration g /m ³ %		Max Ozone Production g/hour lbs/day		Max Oxygen Consumption m ³ /h* l/min* SCFH*			Max Power (kW)	Dimension (W x D x H)	Weight
GM6	150	10 %	360	19	2.4	40	91	3.6	793 x 420 x 602 mm 28.7 x 16.7 x 23.7 in	85 kg 187 lbs
	200	13 %	300	15.9	1.5	25	57			
	250	17 %	240	12.7	0.96	16	36			
	300	20 %	160	8.6	0.54	9	20			
GM12	150	10 %	720	38.1	4.8	80	182	7.2	728 x 424 x 1193 mm 28.7 x 16.7 x 47 in	230 kg 507 lbs
	200	13 %	600	31.7	3.0	50	114			
	250	17 %	480	25.24	1.9	32	73			
	300	20 %	324	17.1	1.1	18	41			
GM18	150	10 %	1080	57.1	7.2	120	273	10.8	728 x 424 x 1569 mm 28.7 x 16.7 x 61.8 in	280 kg 617 lbs
	200	13 %	900	47.6	4.5	75	171			
	250	17 %	720	38.1	2.9	48	109			
	300	20 %	486	25.7	1.6	27	61			
GM24	150	10 %	1440	76.2	9.6	160	364	14.4	992 x 855 x 1639 mm 39 x 34 x 64.3 in	470 kg 1 036 lbs
	200	13 %	1200	63.5	6.0	100	227			
	250	17 %	960	50.8	3.8	64	146			
	300	20 %	648	34.4	2.2	36	82			
GM36	150	10 %	2160	114.4	15.4	240	546	21.6	992 x 855 x 2010 mm 39 x34 x 64.3 in	570 kg 1 256 lbs
	200	13 %	1800	95.2	9.0	150	341			
	250	17 %	1440	76.2	5.8	96	218			
	300	20 %	972	51.4	3.2	54	123			
GM48	150	10 %	2880	152.4	19.2	320	728	28.8	992 x 855 x 1639 mm 39 x 34 x 79.1 in	710 kg 1 565 lbs
	200	13 %	2400	127	12.0	200	455			
	250	17 %	1920	101.6	7.7	128	291			
	300	20 %	1296	68.6	4.3	72	164			

The above figures can vary ± 10 % and apply under the cooling conditions recommended by Primozone

*These values assume gas properties are standardized at 0 °C and atmospheric pressure
**These values assume gas properties are standardized at 68 °F and atmospheric pressure

Primozone Production AB
Terminalvägen 2
246 42 Löddeköpinge Sweden

Primozone Inc.,
5245 West Irlo Bronson
Memorial Highway, Unit #1
Kissimmee, FL 34746

Phone: +46-46-70 45 70
info@primozone.com
www.primozone.com