

HIGH VOLUME COFFEE BREWING SYSTEMS

STATIONARY Series

CBS-72A (FOR COUNTERTOPS)

Twin 6.0 Gallon Station



Shown with 6.0 Gallon LUXUS® Thermal Dispensers (LBD-6)

FETCO® is the category expert and the ONLY manufacturer of ultra high-volume (7-24 Gallon) portable coffee brewing systems for very large scale operations. Due to the high capacity output and reliable performance the CBS-7000 Series is the preferred choice for specification in hotels, stadiums, convention centers and other large venues.



Set it and forget it.

Once your recipe parameters are programmed in, this brewer delivers consistent and repeatable results.



Steam Control.

Efficient, steam containing brew compartments virtually eliminate the need for external ventilation, making this system extremely adaptable to any Foodservice environment.



Expand Your Service.

Brew directly into a High-Capacity LBD Series Thermal Dispenser (sold separately) and transport for high volume coffee or refill service anywhere throughout your venue.

FETCO®
TRUSTED | RELIABLE | QUALITY

Water Specification

Water Inlet
3/8" male flare fitting

Minimum Flow Rate
3 gpm [11.4 lpm]

Water Pressure
20-75 psig [138-517 kPa]


Electrical Configuration

Configuration Code	Heater Configuration	Voltage	Phase	Wires	KW	Electrical Connection	Max Amp Draw	Gallon [Liter] /Hour
US & CANADA								
C72017 ⁽¹⁾	2 x (3x5.0) kW	120/208-240	3	4+G	11.5-15.1	Terminal Block	31.9-36.8	24.0-36.0 [90.8-136.6] ⁽⁴⁾
C72027 ⁽²⁾	2 x (3x5.0) kW	120/208-240	3	4+G	23.0-30.2	Terminal Block	63.8-73.6	36.0-42.0 [136.3-159.0] ⁽⁴⁾
C72037 ⁽¹⁾	2 x (3x10.0) kW	120/208-240	3	4+G	22.8-30.1	Terminal Block	63.2-72.9	54.0-60.0 [204.4-227.1] ⁽⁴⁾
C72047 ⁽¹⁾	2 x (3x10.0) kW	440-480 ⁽³⁾	3	3+G	20.8-30.0	Terminal Block	30.1-36.1	60.0 [227.1] ⁽⁴⁾
C72057 ⁽²⁾	2 x (3x10.0) kW	440-480 ⁽³⁾	3	3+G	41.7-60.0	Terminal Block	60.1-72.2	60.0 [227.1] ⁽⁴⁾
INTERNATIONAL								
C72107	2 x (3 x 5.0) kW	220-240/380-415	3	4+G	12.9-15.1	Terminal Block	19.5-21.3	18.2 [69.0] ⁽¹⁾
C72117	2 x (3 x 10.0) kW	220-240/380-415	3	4+G	25.5-30.1	Terminal Block	38.6-42.1	24.3-30.4 [92.0-115.0] ⁽¹⁾

- (1) With power management.
- (2) Without power management.
- (3) Plus power cord for control, 120 VAC.
- (4) Based on standard factory settings: 7.0 minute brew time; 0% prewet; 200°F water.

Measurements

Height 48 1/2" [123.1 cm]	Width 36" [91.4 cm]	Depth 37" [94.0 cm]	Empty Weight 420 lbs [190.5 kg]	Filled Weight 720 lbs [326.6 kg]	Shipping Weight 659 lbs [298.9 kg]	Shipping Dimensions: 55" x 48" x 42" [139.7 x 121.9 x 106.7 cm]
------------------------------	------------------------	------------------------	------------------------------------	-------------------------------------	---------------------------------------	--



Compatible Dispensers

6.0 Gallon LUXUS® Thermal Dispenser (LBD-6)

D019

Customize Your Brewer

Serving Station for LBD-6 with Drip Tray
Counter for CBS-72A (CTR-72)
Identifier Plates, Acrylic

A018
A020
A069

Cups per Hour*

8oz. **960** 12oz. **640** 16oz. **480** 20oz. **384**

Paper Coffee Filters

23" x 9" (500/Case)

F006

* Approximate based on maximum power setting.

Information

🖱️ fetco.com

✉️ info@fetco.com

📞 847.719.3000
1.800.338.2699 USA
📠 847.719.3001

🏠 Food Equipment Technologies Co.
600 Rose Road
Lake Zurich, IL 60047
USA