


In-Line & Submersible Pumps and Kits


The LVM Series is a whole family of compact, combined submersible and inline pumps and portable pump kits, designed for a whole variety of uses. These models are all capable of pumping hot or cold fresh water, seawater, diesel and anti-freeze. The portable pump kits come complete with lay-flat hose, spray nozzle and battery terminal clips and are ready for use.



Application Capability:	
Flow rate up to 1920 lph (500 gph)	
Pressure up to 0.96 bar (14 psi)	
Operating temperature: 40°C (104°F) Diesel	
80°C (176°F) Water	
Maximum pumping head of 9.7m (32ft)	

Congo In-Line & Submersible Pump


- ◀ Pumps fresh water, sea water, anti-freeze and diesel
- ◀ Diesel refueling and transfer with no spillage
- ◀ High pressure offers excellent flow for Washdown and spraying applications
- ◀ Can be used in series for bore hole pumping and testing
- ◀ Continuous duty



Application Capability:	
Flow rate up to 1080 lph (280 gph)	
Pressure up to 0.96 bar (14 psi)	
Operating temperature: 40°C (104°F) Diesel	
80°C (176°F) Water	
Maximum pumping head of 9.7m (32ft)	

Amazon In-Line & Submersible Pump


- ◀ Pumps fresh water, sea water, anti-freeze and diesel
- ◀ Used by construction equipment OEM's for safe and clean diesel transfer
- ◀ Robust, slim line with clip-on easily cleaned filter
- ◀ Continuous duty



Application Capability:	
Flow rate up to 760 lph (200 gph)	
Pressure up to 0.76 bar (11 psi)	
Operating temperature: 40°C (104°F) Diesel	
80°C (176°F) Water	
Maximum pumping head of 9.7m (32ft)	

Nile In-Line & Submersible Pump


- ◀ Pumps fresh water, sea water and diesel
- ◀ Diesel refueling and transfer with no spillage
- ◀ Agricultural spraying, carboy and drum emptying and transfer
- ◀ Robust, slim line with clip-on easily cleaned filter
- ◀ Continuous duty



Application Capability:	
Flow rate up to 1920 lph (500 gph)	
Pressure up to 0.96 bar (14 psi)	
Operating temperature: 40°C (104°F) Diesel	
80°C (176°F) Water	
Maximum pumping head of 9.7m (32ft)	

Congo Portable Pumping Kit

- ◀ Pumps fresh water, sea water and diesel
- ◀ Supplied complete with 4m (12ft) of lay-flat hose, nozzle and battery clips
- ◀ Agricultural spraying, carboy and drum emptying and transfer
- ◀ Robust, slim line with clip-on easily cleaned filter



Application Capability:	
Flow rate up to 1080 lph (280 gph)	
Pressure up to 0.96 bar (14 psi)	
Operating temperature: 40°C (104°F) Diesel	
80°C (176°F) Water	
Maximum pumping head of 9.7m (32ft)	

Amazon Portable Pumping Kit

- ◀ Pumps fresh water, sea water and diesel
- ◀ Supplied complete with 4m (12ft) of lay-flat hose, nozzle and battery clips
- ◀ Ideal for agricultural, nursery or garden watering and spraying