


# specifications

## RF7.UBR.4.SD

ReFlex Series, 4 Door (Solid), Underbench Fridge

Project: \_\_\_\_\_

Item No: \_\_\_\_\_



CABINET	
Model ID	RF7.UBR.4.SD
SKOPE ID	RF7UBR4-SCLH-SD
Doors	4 × self-closing, lockable, solid swing doors. LH, LH, RH, RH
Internal door opening	4 × door openings: 560mm high × 360mm wide
Shelves	8 × adjustable height shelves: 4 × outside 395mm wide × 510mm deep, 4 × middle 455mm × 510mm deep Note: Bottom shelves supplied floor mounted, additional shelf clips available on request
Worktop	Total thickness 45mm (0.7mm 304 AISI stainless steel over insulating cyclopentane foamed core)
Material	304 AISI stainless steel interior and exterior
PERFORMANCE	
Max. ambient temp.	40°C
Temperature range	1°C to 4°C (adjustable with SKOPE-connect -2°C to 10°C)
Total energy consumption	3.77 kWh/24hr
ELECTRICAL	
Climate class	5 (40°C/40% RH)
Interior lighting	3 × 400mm, 4W LED light (door activated)
Power cord	Supplied with 2.6m, 10 Amp plug and lead
Power supply	220-240 Volts a.c. 50 Hz, single phase supply
Current draw	2.0 Amps (includes unit 1.5 Amps)
REFRIGERATION	
Controller	SCS Connect (SKOPE-connect™ compatible)
Connectivity interface	Bluetooth® wireless technology
Refrigeration system	Side mounted, integral, removable refrigeration cartridge (part number ULKCNI-0022)
Refrigerant	R290 / 95g (natural refrigerant)
Nominal capacity	650 Watts
Heat rejection (Avg/peak)	160 Watts/185 Watts
Drainage	No plumbing required

DIMENSIONS		
	External	Internal
Height	855mm*	570mm
Width	2210mm	1740mm
Depth	700mm	530mm
Floor area	1.55m <sup>2</sup>	
Weight	155kg	
Internal volume	526 litres	

\* With supplied castors fitted. See height variation below

Height variation	
Supplied castors	855mm
Supplied height adjustable legs	865mm - 905mm
No castors or legs	720mm

Dimensional tolerances		
Before installing this cabinet allow the following dimensional tolerances:		
Linear dimensions	Overall cabinet dimensions	
Less than 1 metre	±5mm	
More than 1 metre	-5mm to +10mm	
	Length of multiple cabinets	
	At each joint	At each end wall
Less than 1 metre	±5mm	+15mm
More than 1 metre	-5mm to +10mm	+15mm

Ventilation requirements	
Top	Not required
Sides	Not required
Back	Not required
Bottom	Not required

SKOPE Industries Limited reserve the right to alter specifications without notice. Copyright © 2019 SKOPE Industries Limited

PSS0587 Rev. 2.0 Mar. 2020

### SKOPE INDUSTRIES LIMITED

Australian Freephone: 1800 121 535, New Zealand Freephone: 0800 947 5673

Email: skope@skope.com, Website: www.skope.com