

297352Q



Aluminium telescopic
waterfed handle w/Q
coupling (Q), 1600 - 2780
mm, Ø31 mm, Black



This professional telescopic water-fed handle (1600–2840 mm) has an insulated sleeve for a comfortable grip and a quick-release hose connector. Maximum water pressure, 6 bars.

Technical Data

Item Number	297352Q
Material	Anodised Aluminium Polypropylene Chromium-plated brass
Meets the REACH Regulation (EC) No. 1907/2006	Yes **
SCIP number	e49c50b5-7653-429c- b8f3-803d37b5fefc
Use of phthalates and bisphenol A	No
Box Quantity	5 Pcs.
Quantity per Pallet (80 x 120 x 200 cm)	500 Pcs.
Quantity Per Layer (Pallet)	25 Pcs.
Box Length	1650 mm
Box Width	140 mm
Box Height	85 mm
Product Diameter	31 mm
Length/Depth	1600 mm
Width	31 mm
Height	31 mm
Max. Length	2780 mm
Net Weight	1,02 kg
Weight cardboard	0,082 kg
Tare total	0,082 kg
Gross Weight	1,1 kg
Cubik metre	0,001538 M3
Max. bars pressure	6 Bar
Max usage temperature (non food contact)	50 °C
Min. pH-value in usage concentration	4 pH
Max. pH-value in Usage Concentration	11 pH
GTIN-13 Number	5705022973022
GTIN-14 Number (Box quantity)	15705022973029
Customs Tariff No.	76082020
Country of origin	Denmark

** Lead (Pb, CAS: 7439-92-1) is on the REACH candidate list as a Substance of Very High Concern (SVHC). This product contains lead (Pb) in a concentration above 0.1% w/w. Consequently the REACH Regulation (EC) No. 1907/2006 require Vikan to notify our customers of the content of lead. This product is registered in the EU SCIP database. Please find SCIP number above.