


CANDLE

4W | 300 lm | 2200K

CAND-4W-2200K-E12-NT-120V


Candle 4W 2200K E12 Non-Tinted US LED Bulb

tala®



PHYSICAL

Bulb diameter:	1 3/8 in
Bulb length:	3 7/8 in
Glass shape:	C11
Base:	E12
Materials:	glass and nickel
Glass finish:	Clear
Weight:	0.03 lbs
Max. working temp.:	Max. 40°C
IP rating:	IP54




ELECTRICAL

Power:	4W
Current:	0.04 A
Voltage:	110-120V~ V
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	75 lm/W
Lifetime:	30000 hrs

ILLUMINATION

CCT:	2200K
Lumens:	300 lm
Incandescent equiv.:	28W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	65
TM30 - Rg	100
TM30 - Rf	90

IES/LDT photometry files and product photography available on request



DIMMING

Dimmable 0-100%
Recommended dimmer: Lutron Diva DVELV-300P
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,
Suite 300, Rockville, MD 20850

WARRANTY

2 years

talalighting.com | hello@tala.co.uk | +1 (240) 724-8111

EAN

5061046291970

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights