

PLUTO

3W | 180 lm | 2200K

PLUT-3W-2200K-E12-T-120V

Pluto 3W 2200K E12 Tinted US LED Bulb


tala®

The small, round-shaped Pluto light bulb by Tala features a traditional filament arrangement encased in an iron-tinted glass, delivering a warm, rich glow. Fitted with an E12 base, it is compatible with a variety of smaller fixtures, such as table lamps or wall sconces. Complete with energy-efficient LED technology, the Pluto bulb lasts an average of 5-10 years based on daily usage.




PHYSICAL

Bulb diameter:	1 6/8in
Bulb length:	3 1/8in
Glass shape:	G14
Base:	E12
Materials:	Glass & nickel
Glass finish:	Tinted
Weight:	16g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54



— C0/C80
— C0/C270

IES/LDT photometry files
and product photography
available on request



ELECTRICAL

Power:	3W
Current:	0.03A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	60 lm/W
Lifetime:	30,000 hrs

ILLUMINATION

CCT:	2200K
Lumens:	180 lm
Incandescent equiv.:	19W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	80
TM30 - Rg	97
TM30 - Rf	90



Intertek



DIMMING

Dimmable 0-100%
Recommended dimmer: Lutron Diva DVELV-300P
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,
Suite 300, Rockville, MD 20850

LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 10
Gross weight: 30	Gross weight: 0.32
L 2 x W 2 x H 3 4/8in	L 10 5/8 x W 4 3/8 x H 4in

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

WARRANTY

2 years

Specification subject to change without
notice. Refer to our website for the most
recent product documentation. Tala
designs in the EU/UK are protected by
registered and or unregistered design rights

EAN

5060400151226