
## **PLUTO**

# tala


### 3W | 240 lm | 2500K PLUT-3W-2500K-E12-NT-120V Pluto 3W 2500K E12 Non-Tinted US LED Bulb

The small, round-shaped Pluto light bulb by Tala features a traditional filament arrangement encased in a clear glass surround. This bulb delivers a warm, rich glow and its E12 base makes it compatible with a variety of smaller fixtures, such as table lamps or wall sconces. Complete with energy-efficient LED technology, the Pluto bulb lasts an average of 5-10 years based on daily usage.





IES/LDT photometry files and product photography available on request



#### **PHYSICAL**

Bulb diameter: 1 6/8in
Bulb length: 3 1/8in
Glass shape: G14
Base: E12

Materials: Glass & nickel

Glass finish: Clear Weight: 16g

Max. working temp.: -5°C to 40°C IP rating: IP54

#### **ELECTRICAL**

 Power:
 3W

 Current:
 0.03A

 Voltage:
 110-120V~

 Frequency:
 50/60Hz

 Power factor:
 0.9

 Efficiency:
 80 lm/W

 Lifetime:
 30,000 hrs

#### **ILLUMINATION**

CCT-2500K Lumens: 240 lm Incandescent equiv.: 24W <5% Flicker: Beam angle: 360° Light source: LED CRI: 95Ra 70 R9: TM30 - Rg 98 TM30 - Rf 90







**DIMMING** Dimmable 0-100%

Recommended dimmer: Lutron Diva DVELV-300P (For a full list of recommended and compatible

dimmers see website)

LOGISTICAL Unit Packaging

 Unit Packaging
 Outer Carton

 PC/Ctn: 1
 PC/Ctn: 10

 Gross weight: 30
 Gross weight: 0.32

 L 2 x W 2 x H 3 4/8in
 L 10 5/8 x W 4 3/8 x H 4in

WARRANTY 2 years

**EAN** 5060400151233

Tala Energy Ltd. 25b Vyner Street, London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place, Suite 300, Rockville, MD 20850

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights