

GLOBE

6W | 600 lm | 2500K

GLOB-6W-2500K-E26-NT-120V

Globe 6W 2500K E26 Non-Tinted US LED Bulb


tala

The Globe light bulb by Tala features eight exposed sapphire substrate filaments, which come together in this traditional Edison-style shape. The effect is a warm, ambient light in a E26 base that makes the Globe ideal to fit into new or existing fixtures. Suitable for display or behind a shade, the Globe is complete with energy efficient LED technology, lasting an average of 5-10 years based on daily usage.




PHYSICAL

Bulb diameter:	2 3/8in
Bulb length:	4 2/8in
Glass shape:	A19
Base:	E26
Materials:	Glass & nickel
Glass finish:	Clear
Weight:	31g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54



— C0/C80
— C0/C20

IES/LDT photometry files
and product photography
available on request



ELECTRICAL

Power:	6W
Current:	0.05A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	100 lm/W
Lifetime:	30,000 hrs

ILLUMINATION

CCT:	2500K
Lumens:	600 lm
Incandescent equiv.:	48W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	70
TM30 - Rg	98
TM30 - Rf	90



DIMMING

Dimmable 0-100%
Recommended dimmer: Lutron Diva DVELV-300P
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 10
Gross weight: 70	Gross weight: 0.65
L 2 4/8 x W 2 4/8 x H 5 1/8in	L 13 3/8 x W 5 4/8 x H 5 6/8in

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

WARRANTY

2 years

Specification subject to change without
notice. Refer to our website for the most
recent product documentation. Tala
designs in the EU/UK are protected by
registered and or unregistered design rights

EAN

5060400151264