


GLOBE

6W | 480 lm | 2200K

GLOB-6W-2200K-E26-NT-120V


Globe 6W 2200K E26 Non-Tinted US LED Bulb

tala®



PHYSICAL

| | |
|---------------------|------------------|
| Bulb diameter: | 2 3/8 in |
| Bulb length: | 4 1/4 in |
| Glass shape: | A19 |
| Base: | E26 |
| Materials: | glass and nickel |
| Glass finish: | Clear |
| Weight: | 0.07 lbs |
| Max. working temp.: | Max. 40°C |
| IP rating: | IP54 |




ELECTRICAL

| | |
|---------------|-------------|
| Power: | 6W |
| Current: | 0.06 A |
| Voltage: | 110-120V~ V |
| Frequency: | 50/60Hz |
| Power factor: | 0.9 |
| Efficiency: | 80 lm/W |
| Lifetime: | 30000 hrs |

ILLUMINATION

| | |
|----------------------|--------|
| CCT: | 2200K |
| Lumens: | 480 lm |
| Incandescent equiv.: | 41W |
| Flicker: | <5% |
| Beam angle: | 360° |
| Light source: | LED |
| CRI: | 95Ra |
| R9: | 70 |
| TM30 - Rg | 100 |
| TM30 - Rf | 90 |

IES/LDT photometry files
and product photography
available on request



DIMMING

Dimmable 0-100%
Recommended dimmer: Lutron Diva DVELV-300P
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,
Suite 300, Rockville, MD 20850

WARRANTY

2 years

talalighting.com | hello@tala.co.uk | +1 (240) 724-8111

EAN

5061046291932

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights