

TOTEM I

3W | 180 lm | 2200K

TOTM-I-3W-2200K-E12-T-120V

Totem I 3W 2500K E12 Tinted US LED Bulb


tala®

The Totem I light bulb by Tala is a small, linear industrial-style light bulb, perfect for illuminating desk lamps or as part of a chandelier. Fitted with a E12 base and finished with an iron-tinted glass casing, it serves a functional purpose with excellent light output. Engineered to last for 5-10 years based on daily usage



PHYSICAL

Bulb diameter:	1in
Bulb length:	3 6/8in
Glass shape:	T8
Base:	E12
Materials:	Glass & nickel
Glass finish:	Tinted
Weight:	14g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54




ELECTRICAL

Power:	3W
Current:	0.03A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	60 lm/W
Lifetime:	30,000 hrs

ILLUMINATION

CCT:	2200K
Lumens:	180 lm
Incandescent equiv.:	19W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	80
TM30 - Rg	100
TM30 - Rf	94

IES/LDT photometry files and product photography available on request



DIMMING

Dimmable 0-100%
Recommended dimmer: Lutron Diva DVELV-300P
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,
Suite 300, Rockville, MD 20850

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 10
Gross weight: 20	Gross weight: 0.25
L 1 1/8 x W 1 1/8 x H 3 7/8in	L 6 6/8 x W 2 6/8 x H 4 4/8in

WARRANTY

2 years

EAN

5060400151417

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights