

VORNOI I

2W | 100 lm | 2200K

VORN-I-2W-2200K-E26-T-120V

Voronoï I 2W 2200K E26 Tinted US LED Bulb


tala®

The Voronoï I bulb was designed to imitate forms and shapes found in nature. Mouth-blown and assembled by hand to the highest standards by skilled artisans, this sculptural bulb is best when hung in clusters of three or displayed individually in decorative fixtures. Fitted with E26 base cap.




PHYSICAL

Bulb diameter:	4 7/8in
Bulb length:	6 7/8in
Glass shape:	G40*
Base:	E26
Materials:	Glass & nickel
Glass finish:	Tinted
Weight:	160g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54



— C0/C80
— C0/C20

IES/LDT photometry files
and product photography
available on request



ELECTRICAL

Power:	2W
Current:	0.02A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	50 lm/W
Lifetime:	15,000 hrs

ILLUMINATION

CCT:	2200K
Lumens:	100 lm
Incandescent equiv.:	12W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	80
TM30 - Rg	100
TM30 - Rf	94



DIMMING

Dimmable 0-100%
Recommended dimmer: Lutron Diva DVELV-300P
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,
Suite 300, Rockville, MD 20850

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 6
Gross weight: 190	Gross weight: 4.485
L 7 4/8 x W 5 7/8 x H 9 5/8in	L 21 2/8 x W 14 1/8 x H 9 4/8in

WARRANTY

2 years

EAN

5060400152124

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights