

# VORONOI II

3W | 150 lm | 2200K

VORN-II-3W-2200K-E26-T-120V

Voronoi II 3W 2200K E26 Tinted US LED Bulb


tala®

The Voronoi II is Tala's most recognised and best-selling light bulb, revered for its striking shape and subtle light output. With its elongated form and droplet shape, the lamp captures the beauty of the Fibonacci sequence as its singular filament wraps around a central glass column. Best paired with Tala's Brass pendant. Fitted with E26 base cap.




## PHYSICAL

Bulb diameter:	6 4/8in
Bulb length:	10 6/8in
Glass shape:	A52*
Base:	E26
Materials:	Glass & nickel
Glass finish:	Tinted
Weight:	250g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54



— C0/C80  
— C0/C20

IES/LDT photometry files  
and product photography  
available on request



## ELECTRICAL

Power:	3W
Current:	0.03A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	50 lm/W
Lifetime:	15,000 hrs

## ILLUMINATION

CCT:	2200K
Lumens:	150 lm
Incandescent equiv.:	16W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	80
TM30 - Rg	100
TM30 - Rf	94



## DIMMING

Dimmable 0-100%  
Recommended dimmer: Lutron Diva DVELV-300P  
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,  
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,  
Suite 300, Rockville, MD 20850

## LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 3
Gross weight: 500	Gross weight: 1.9
L 8 1/8 x W 7 4/8 x H 13 6/8in	L 25 5/8 x W 9 x H 13 2/8in

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

## WARRANTY

2 years

Specification subject to change without  
notice. Refer to our website for the most  
recent product documentation. Tala  
designs in the EU/UK are protected by  
registered and or unregistered design rights

## EAN

5060400152131