

SPHERE II

6W | 480 lm | 2000-2800K

SPHR-G75-6W-2000-2800K-E26-MP-120V

Sphere Medium 6W WoD 2000K to 2800K E26 Matte Porcelain US LED Bulb


tala.

Tala's Sphere II light bulb is a refined and effective light source. Boasting Dim to Warm and flicker-free behaviour, Sphere I can dim from a cool, bright light, to its lowest setting while maintaining a warm, amber glow. Fitted with an E26 base cap, this is a stylish solution for any number of table, floor or ceiling lights.



PHYSICAL

Bulb diameter:	3in
Bulb length:	4 3/8in
Glass shape:	G24
Base:	E26
Materials:	Glass & nickel
Glass finish:	Matte White
Weight:	59g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54




ELECTRICAL

Power:	6W
Current:	0.06A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	75 lm/W
Lifetime:	15,000 hrs

ILLUMINATION

CCT:	2000-2800K
Lumens:	480 lm
Incandescent equiv.:	41W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	80
TM30 - Rg	101
TM30 - Rf	94

IES/LDT photometry files and product photography available on request



DIMMING

Dimmable 0-100%
Recommended dimmer: Lutron Diva DVELV-300P
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,
Suite 300, Rockville, MD 20850

LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 10
Gross weight: 80	Gross weight: 1
L 3 1/8 x W 3 1/8 x H 4 6/8in	L 16 4/8 x W 6 6/8 x H 5 4/8in

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

WARRANTY

2 years

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights

EAN

5060400158706