

US G9 3000K


4W | 420 lm | 3000K
G9-4W-3000K-RA97-120V

tala[®]




PHYSICAL

Bulb dimension:	6/8 in
Bulb length:	2 2/8 in
Glass shape:	T6
Base:	G9
Materials:	Ceramic & Polycarbonate
Glass finish:	Lightly frosted
Weight:	0.04 lbs
Max. working temp.:	Max. 40°C
IP rating:	IP20



IES/LDT photometry files
and product photography
available on request



ELECTRICAL

Power:	4W
Current:	0.04 A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor	0.9
Efficiency:	105 lm/W
Lifetime:	15,000 hrs

ILLUMINATION

CCT:	3000K
Lumens:	420 lm
Incandescent equiv.:	37 W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	97Ra
R9:	90
TM30 - Rg	100
TM30 - Rf	90



DIMMING

Dimmable 0-100%
Recommended dimmer: Tala Rotary Wall Dimmer
(For a full list of recommended and compatible
dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala North America Inc.
C/O LH Frishkoff & Company
546 5th Avenue, FL 9
New York NY 10036
United States

talalighting.com | hello@tala.co.uk | +1 (240) 724-8111

WARRANTY

2 years

EAN

5061046299303

Specification subject to change without
notice. Refer to our website for the most
recent product documentation. Tala
designs in the EU/UK are protected by
registered and or unregistered design rights