

INSTALLATION INSTRUCTIONS



Step 6: Suspend LED Gear Tray

Following release of LED gear tray in Step 5, the gear tray will suspend from plastic tethers during housing installation. Remove end plug(s) to accommodate wiring connections as required.







Step 7: Bring in Power Bring wiring into housing as required



Step 9: Reinstall LED Gear Tray

Reinstall LED gear tray to plastic mounting clips



Step 10: Reinstall Lens

Reinstall lens taking care to properly seat lens in the lens retention lip and fully secure all latches.

Step 11: Turn on Electrical Power

Connect power and confirm proper operation.

NOTE: For an improved water tight seal, apply silicone sealant to both sides of O-ring as shown.

Step 8: Make Electrical Connections

Make electrical connections to LED driver. Connect Line (Black), Neutral (White) and Ground (Green) connections

1-866-967-4547 WWW.ORILIS.COM



INSTALLATION INSTRUCTIONS

ORTLIS IFD VAPOR TIGHT FIXTURE

SAFETY WARNINGS IMPORTANT SAFETY INFORMATION





Before you begin.

Read these instructions completely & carefully.



WARNING Risk of electrical shock. Disconnect power before servicing or installing Avertissement - Risque de choc électrique. Coupez l'alimentation avant l'entretien ou l'installation



WARNING Risk of injury. Wear safety glasses and gloves during installation and servicing. Avertissement - Risque de blessure. Porter des lunettes de sécurité et des gants lors de l'installation et l'entretien

INSTALLATION



Step 1: Inspect Product

Inspect the product upon receipt and notify the delivery carrier of any damage that may have occurred during shipment.



Step 2: Install Mounting Brackets

Identify locations and securely attach mounting brackets to mounting surface. Use two (2) brackets for 4' units. Mounting brackets engage the housing at any point along its length not obstructed by latches. Mount brackets evenly to span at least 60% of the length of the housing.



Step 4: Mount Housing

Insert one side of housing into mounting brackets, taking care to assure that bracket engages housing lens retention lip without distorting gasket. Rotate housing up and press other side of mounting brackets to similarly engage on the other side until bracket clicks into place. Verify that the housing is fully supported.





Release LED gear tray by squeezing white plastic mounting clips. LED gear tray will suspend from plastic tethers during housing installation.

WWW.ORILIS.COM